# Weierstraß-Institut für Angewandte Analysis und Stochastik

im Forschungsverbund Berlin e.V.

Preprint

ISSN 0946 - 8633

## A complete-damage problem at small strains

Guy Bouchitté<sup>1</sup>, Alexander Mielke<sup>2,3</sup> and Tomáš Roubíček<sup>4,5</sup>

- <sup>1</sup> Départemant de Mathématiques, Université du Sud Toulon-Var, BP 132, F-83957 La Garde Cedex, France, E-Mail: bouchitte@univ-tln.fr
- <sup>2</sup> Weierstraß-Institut für Angewandte Analysis und Stochastik, Mohrenstraße 39, 10117 Berlin, Germany, E-Mail: mielke@wias-berlin.de
- <sup>3</sup> Institut für Mathematik, Humboldt-Universität zu Berlin, Rudower Chaussee 25, 12489 Berlin-Adlershof, Germany
- <sup>4</sup> Mathematical Institute, Charles University, Sokolovská 83, CZ–18 675 Praha 8, Czech Republic, E-Mail: roubicek@karlin.mff.cuni.cz
- <sup>5</sup> Institute of Information Theory and Automation, Academy of Sciences, Pod vodárenskou věží 4, CZ–18208 Praha 8, Czech Republic

submitted: 30th May 2007

No. 1228 Berlin 2007



<sup>2000</sup> Mathematics Subject Classification. 35K65, 35K85, 49S05, 74C05, 74R05.

 $Key\ words\ and\ phrases.$  Inelastic damage; small strain; variational inequality; energetic formulation.

Edited by Weierstraß-Institut für Angewandte Analysis und Stochastik (WIAS) Mohrenstraße 39 10117 Berlin Germany

Fax:+ 49 30 2044975E-Mail:preprint@wias-berlin.deWorld Wide Web:http://www.wias-berlin.de/

#### Abstract

The complete damage of a linearly-responding material that can thus completely disintegrate is addressed at small strains under time-varying Dirichlet boundary conditions as a rate-independent evolution problem in multidimensional situations. The stored energy involves the gradient of the damage variable. This variable as well as the stress and energies are shown to be well defined even under complete damage, in contrast to displacement and strain. Existence of an energetic solution is proved, in particular, by detailed investigating the  $\Gamma$ -limit of the stored energy and its dependence on boundary conditions. Eventually, the theory is illustrated on a one-dimensional example.

## 1 Introduction

Damage, as a special sort of *inelastic response* of solid materials, results from microstructural changes under mechanical load. important relevance in applications and routine computational simulations using various models are performed, although mostly without being supported by rigorous mathematical and numerical analysis. This convincingly indicates the mathematical non-triviality of the damage problem.

We will consider damage as a *rate-independent* process by neglecting all rate dependent processes like viscosity and inertia, This is often, although not always, an appropriate concept and has applications in a variety of industrially important materials, especially to concrete [13, 16, 33], filled polymers [10], or filled rubbers [18, 24, 25]. Being rate-independent, it is necessarily an *activated* process, i.e. to trigger a damage the mechanical stress must achieve a certain activation threshold. The mathematical difficulty is reflected that only local-in-time existence for a simplified scalar model or for a rate-dependent 0- or 1-dimensional model has been recently performed in [2, 9, 14, 15]. The 3-dimensional situation was investigated in [27, 28, 11] with the focus to incomplete damage. The main focus of this paper is on *complete damage*, i.e. the material can completely *disintegrate* and its displacement completely loses any sense on such regions. The related mathematical troubles are immediately expected and specific mathematical techniques urgently needed.

We consider a nonhomogeneous anisotropic material but confine ourselves to a materials with *linear elastic response* and an *isotropic damage* using only one scalar damage parameter under *small strains* (as in [1, 2, 13, 17]) and the *gradient-ofdamage* theory [8, 13, 16, 17, 22, 23, 34] expressing a certain nonlocality in the sense that damage of a particular spot is to some extent influenced by its surrounding, leading to possible hardening or softening-like effects, and introducing a certain internal length scale eventually preventing damage microstructure development. From the mathematical viewpoint, the damage gradient has a compactifying character and opens possibilities for the successful analysis of the model. Anyhow, some investigations are still possible without gradient of damage, as shown in [11] for incomplete damage, leading to a possible microstructure in the damage profile.

To present a relevant formulation of the rate-independent evolution of the damage, in Section 2 we first scrutinize the static problem with a prescribed damage profile under a prescribed boundary condition. Then, in Section 3, the energetic solution to the evolution problem is formulated in terms of the damage profile and stress (or, equivalently, of the shape of completely damaged part and the strain in the rest) and its existence is proved with help of results from [26, 27, 28]. Eventually, an illustrative one-dimensional example is presented in some detail in Section 4.

## 2 Static problem and its perturbation analysis

We consider a bounded Lipschitz domain  $\Omega \subset \mathbb{R}^d$ , an open nonempty part  $\Gamma \subset \partial\Omega$  of its boundary  $\partial\Omega$  on which we prescribe the *Dirichlet boundary condition*  $w \in W^{1/2,2}(\Gamma; \mathbb{R}^d)$ . We use the standard notation  $W^{k,p}$  for Sobolev or Sobolev-Slobodetskiĭ spaces whose *p*-power of the *k*-order derivatives is integrable, allowing for k > 0 non-integer. Further, we will consider  $\zeta \in W^{1,r}(\Omega)$  valued in [0, 1] as a scalar *damage parameter* assumed prescribed in this section but later, in Sections 3 and 4, it will evolve in time. The meaning of  $\zeta$  is the portion of the undamaged material, i.e.  $\zeta(x) = 1$  means that the material is completely undamaged at the current point  $x \in \Omega$  while  $\zeta(x) = 0$  means just the opposite, i.e. complete damage at x. Let us abbreviate the set of admissible damage profiles

$$Z := \left\{ \zeta \in W^{1,r}(\Omega); \quad \zeta(\cdot) \in [0,1] \text{ a.e. on } \Omega \right\}$$

$$(2.1)$$

and denote the set of the complete damage by

$$N_{\zeta} := \left\{ x \in \Omega; \quad \zeta(x) = 0 \right\}, \tag{2.2}$$

then  $u: \Omega \setminus N_{\zeta} \to \mathbb{R}^d$  will denote a displacement. Naturally, we do not consider u defined on the damaged part  $N_{\zeta}$  where the material is completely disintegrated.

Our aim is to investigate a minimization problem that can be *formally* written as

minimize 
$$V_0(u,\zeta) := \int_{\Omega} \zeta(x)\varphi(x, [e(u)](x)) + \frac{\kappa(x)}{r} |\nabla\zeta(x)|^r dx$$
  
subject to  $u$  is a displacement such that  $u|_{\Gamma} = w$ . (2.3)

where  $\kappa : \Omega \to \mathbb{R}$  is a so-called factor of influence of damage and  $\varphi : \Omega \times \mathbb{R}^{d \times d}_{sym} \to \mathbb{R}$ is a Carathéodory function such that  $\varphi(x, \cdot) : \mathbb{R}^{d \times d}_{sym} \to \mathbb{R}$  is a quadratic coercive form on the set of the symmetric  $(d \times d)$ -matrices  $\mathbb{R}^{d \times d}_{sym}$  describing the elastic stored energy, say

$$\varphi(e) = \frac{1}{2} \sum_{i,j,k,l=1}^{d} \mathbb{C}_{ijkl}(x) e_{ij} e_{kl}, \qquad (2.4)$$

and where, as usual in linear elasticity (where small deformations are assumed), e(u) denotes the linearized strain tensor, called the *small-strain tensor*:

$$e(u) = \frac{1}{2} (\nabla u)^{\top} + \frac{1}{2} \nabla u.$$
 (2.5)

The 4-th order tensor  $\mathbb{C}(x)$  of *elastic moduli* satisfies the usual symmetries, uniform positive-definiteness and boundedness:

$$\forall (a.a.) x \in \Omega : \qquad \mathbb{C}_{ijkl}(x) = \mathbb{C}_{jikl}(x) = \mathbb{C}_{klij}(x), \qquad (2.6a)$$

$$\exists \eta > 0 \quad \forall (a.a.) \ x \in \Omega \quad \forall e \in \mathbb{R}^{d \times d}_{\text{sym}} : \quad \sum_{i,j,k,l=1} \mathbb{C}_{ijkl}(x) e_{ij} e_{kl} \ge \eta |e|^2, \tag{2.6b}$$

$$\mathbb{C}_{ijkl} \in L^{\infty}(\Omega). \tag{2.6c}$$

The term  $\frac{1}{r}\kappa(x)|\nabla\zeta(x)|^r$  models a certain nonlocality as mentioned in Sect. 1 and is quite often used in literature [8, 13, 16, 17, 22, 23]. The scalar coefficient  $\kappa$ determines a certain length-scale of the possible fine structure that might develop in a damage profile and, in accord with the adopted nonhomogeneous-material concept, is assumed possibly x-dependent and to satisfy

$$\kappa \in L^{\infty}(\Omega), \qquad \underset{x \in \Omega}{\operatorname{ess \, inf}} \ \kappa(x) > 0.$$
(2.7)

In particular, for the usage in Sect. 3, we are interested in a certain stability of this problem with respect to perturbations of the damage profile  $\zeta$  with respect to the weak  $W^{1,r}(\Omega)$ -topology. Here, in accord with [27], we consider r > d. Then  $N_{\zeta}$ from (2.2) is closed in  $\Omega$  since  $\zeta \in W^{1,r}(\Omega) \subset C(\overline{\Omega})$  with r > d. Let us remark that the theory of incomplete damage was alternatively developed also for  $\zeta \in W^{\alpha,2}(\Omega)$ with  $\alpha > 0$  in [28] but it is not obvious how it would be transferred to complete damage because, in the following consideration, we will heavily rely on the compact embedding  $\zeta \in W^{1,r}(\Omega) \subset C(\overline{\Omega})$ .

Let us agree that occasionally we will omit the explicit x-dependence of  $\varphi$  for brevity.

#### 2.1 Regularized problem

The mentioned essential trouble with (2.3) is that the displacement u has no obvious meaning on the completely damaged part  $N_{\zeta}$ , which is why (2.3) must be considered only formally, as said above. For the purpose of further analysis based on the results from [27, Sect.4] and, perhaps even more importantly, for a conceptual numerical strategies (see Remark 3.10 below), it is relevant to investigate limit behavior (for  $\varepsilon \to 0+$ ) of a regularized problem

minimize 
$$V_{\varepsilon}(u,\zeta) := \int_{\Omega} (\zeta(x) + \varepsilon) \varphi(x, [e(u)](x)) + \frac{\kappa(x)}{r} |\nabla \zeta(x)|^r dx$$
  
subject to  $u \in W^{1,2}(\Omega; \mathbb{R}^d), \quad u|_{\Gamma} = w.$  (2.8)

Obviously,  $V_0$  from (2.3) is just  $V_{\varepsilon}$  for  $\varepsilon = 0$ . For  $\varepsilon \ge 0$ , let us define

$$G_{\varepsilon}(u,\zeta) := \begin{cases} V_{\varepsilon}(u,\zeta) & \text{if } u|_{\Gamma} = w \text{ and } \zeta \in Z, \\ +\infty & \text{elsewhere,} \end{cases}$$
(2.9)

where Z is from (2.1). The theory for complete damage developed in [27, Sect.4] relies on a substantial stored energy defined, for a given damage profile  $\zeta$  and a hard-device loading w, as the  $\Gamma$ -limit of the sequence  $\{g_{\varepsilon}\}_{\varepsilon>0}$  (considering only a countable number of  $\varepsilon$  converging to 0) where

$$g_{\varepsilon}(\zeta) := \min_{u \in W^{1,2}(\Omega; \mathbb{R}^d)} G_{\varepsilon}(u, \zeta).$$
(2.10)

Let us note that the minimum in (2.10) is attained by the standard coercivity arguments.

Thanks to the regularization term  $\int_{\Omega} \frac{\kappa}{r} |\nabla \zeta|^r dx$ , the relevant topology used for the damage variable  $\zeta$  will be the weak topology of  $W^{1,r}(\Omega)$ . It is important for the subsequent analysis that we assumed r > d so that the weak convergence of a sequence  $\{\zeta_{\varepsilon}\}$  (denoted as usual by  $\zeta_{\varepsilon} \rightharpoonup \zeta$ ) implies the uniform convergence as continuous functions on  $\overline{\Omega}$ .

Recall now that the sequence  $\{g_{\varepsilon}\}_{\varepsilon>0}$  is said to be sequentially  $\Gamma$ -convergent to  $\mathfrak{g}$  for the weak topology of  $W^{1,r}(\Omega)$  if the following properties hold:

(i) lower bound: for every sequence  $\{\zeta_{\varepsilon}\}_{\varepsilon>0}$  converging weakly to  $\zeta \in \mathbb{Z}$ , we have:

$$\liminf_{\varepsilon \to 0} g_{\varepsilon}(\zeta_{\varepsilon}) \ge \mathfrak{g}(\zeta). \tag{2.11}$$

(ii) recovering sequence: for every  $\zeta \in Z$  there exists a sequence  $\{\zeta_{\varepsilon}\}_{\varepsilon>0} \subset Z$  converging to  $\zeta$  such that

$$\limsup_{\varepsilon \to 0} g_{\varepsilon}(\zeta_{\varepsilon}) \le \mathfrak{g}(\zeta).$$
(2.12)

When properties (i) and (ii) are satisfied, we write  $\mathfrak{g} = \Gamma - \lim_{\varepsilon \to 0} g_{\varepsilon}$ . In our case the sequence  $\{g_{\varepsilon}\}_{\varepsilon>0}$  is monotone and the existence of a  $\Gamma$ -limit is guaranteed by the following lemma:

**Lemma 2.1** (See [6].) Assume that  $g_{\varepsilon}$  is nonincreasing with respect to  $\varepsilon$  and let  $g_0(\zeta) := \inf_{\varepsilon>0} g_{\varepsilon}(\zeta)$ . Then  $\{g_{\varepsilon}\}_{\varepsilon>0}$  does  $\Gamma$ -converge to the lower semicontinuous envelope of  $g_0$  with respect to the weak topology on  $W^{1,r}(\Omega)$ .

In our case, the computation of  $g_0$  is quite easy: by using (2.10) and by switching the infimum in  $\varepsilon$  with the infimum in u, one has

$$g_0(\zeta) = \inf_{\varepsilon > 0} \inf_{u \in W^{1,2}(\Omega)} G_{\varepsilon}(u,\zeta) = \inf_{u \in W^{1,2}(\Omega)} \inf_{\varepsilon > 0} G_{\varepsilon}(u,\zeta) = \inf_{u \in W^{1,2}(\Omega)} G_0(u,\zeta) . \quad (2.13)$$

As a consequence of Lemma 2.1,  $g_0$  will be the  $\Gamma$ -limit we are looking for provided  $g_0$  given above enjoys the lower semicontinuity property. Unfortunately, as shown in Section 2.2, this property fails and the determination of  $\mathfrak{g}$  is a more involved problem which we are going to solve later, see Proposition 2.10.

Also note that  $\mathfrak{g}$  is always bounded from below because we do not consider any external dead loading like gravity force; obviously, we always have  $\mathfrak{g} \geq 0$ . In fact, due to the regularization term  $\int_{\Omega} \frac{\kappa}{r} |\nabla \zeta|^r dx$  and (2.7), we have even the coercivity  $\mathfrak{g}(\zeta) \geq (\operatorname{ess\,inf} \frac{\kappa}{r}) \|\nabla \zeta\|_{L^r(\Omega;\mathbb{R}^d)}^r$  and therefore the sequential  $\Gamma$ -limit  $\mathfrak{g}$  is weakly lower semicontinuous.

**Remark 2.2** (Mosco convergence.) In fact, later in the proof of (3.21) we will show even strong convergence of recovery sequences. This allows for replacing the weak topology in (ii) by the strong one, which means that the convergence of  $g_{\varepsilon}$  to  $\mathfrak{g}$  in the sense of U. Mosco [32].

#### 2.2 A 1-dimensional counterexample

Let us show a 1-dimensional example of a failure of weak lower-semicontinuity of  $g_0$ . Being inspired by [3, Example 3], let us consider d = 1, the interval  $\Omega := (-1, 1)$ , the Dirichlet condition w prescribed on  $\Gamma := \{-1, 1\}$  as w(x) := x,  $\varphi(e) = \frac{1}{2}|e|^2$ , and the damage profile

$$\zeta(x) := \left| x \right|^{\alpha} \quad \text{with} \quad 1 - \frac{1}{r} < \alpha < 1.$$
(2.14)

Direct calculations easily shows that  $\zeta \in W^{1,r}(\Omega)$ . Then we consider the sequence  $\{\zeta_n\}_{n\in\mathbb{N}}$  of

$$\zeta_n(x) := \left(\max\left(0, |x| - \frac{1}{n}\right)\right)^{\alpha}.$$
(2.15)

Obviously  $\zeta_n \to \zeta$  for  $n \to \infty$  even in the norm topology of  $W^{1,r}(\Omega)$ . Moreover,  $g_0(\zeta_n) = 0$  because obviously  $g_0(\zeta_n) = G_0(u_n, \zeta_n) = 0$  for the piecewise affine displacement profile

$$u_n(x) := \begin{cases} -1 & \text{for } -1 \le x \le -\frac{1}{n}, \\ nx & \text{for } -\frac{1}{n} < x < \frac{1}{n}, \\ 1 & \text{for } \frac{1}{n} \le x \le 1. \end{cases}$$
(2.16)

Therefore  $\mathfrak{g}(\zeta) = 0$  because

$$0 \le \mathfrak{g}(\zeta) \le \liminf_{n \to \infty} G_0(u_n, \zeta_n) = \lim_{n \to \infty} 0 = 0.$$
(2.17)

On the other hand, we will show that  $\inf_{u \in W^{1,2}(\Omega;\mathbb{R}^d)} G_0(u,\zeta) > 0$ . Since  $\alpha < 1$ ,  $\| | \cdot |^{-\alpha} \|_{L^1(\Omega)} = 2/(1-\alpha)$  and, in particular,  $1/\zeta : x \mapsto |x|^{-\alpha} \in L^1(\Omega)$ . We realize that in our 1-dimensional case we have  $\frac{d}{dx}u = e(u)$  and, by Young's inequality, the estimate

$$\left\|\frac{\mathrm{d}u}{\mathrm{d}x}\right\|_{L^{1}(\Omega)} = \sup_{\|v\|_{L^{\infty}(\Omega)} \le 1} \int_{\Omega} \frac{\mathrm{d}u}{\mathrm{d}x} v \,\mathrm{d}x$$
$$\leq \sup_{\|v\|_{L^{\infty}(\Omega)} \le 1} \int_{\Omega} \frac{\zeta}{2} \left|\frac{\mathrm{d}u}{\mathrm{d}x}\right|^{2} + \frac{|v|^{2}}{2\zeta} \,\mathrm{d}x \le \int_{\Omega} \zeta \varphi(e(u)) \,\mathrm{d}x + \frac{1}{2} \left\|\frac{1}{\zeta}\right\|_{L^{1}(\Omega)}. \tag{2.18}$$

This shows that each set of u's that has a bounded energy is inevitably bounded in  $W^{1,1}(\Omega)$ . Note that both subintervals (-1,0) and (0,1) which a.e. cover  $\Omega = (-1,1)$ , are connected with  $\Gamma$  where the boundary conditions are fixed so that the boundedness of u's in  $L^{\infty}(\Omega)$  is also granted. In particular, it holds for a minimizing sequence  $\{u_n\}_{n\in\mathbb{N}}$  for  $G_0(\cdot,\zeta)$ . Hence it contains a subsequence converging weakly<sup>\*</sup> in BV( $\Omega$ ), the space of bounded-variation functions, to some limit u. In particular,  $\frac{\mathrm{d}}{\mathrm{d}x}u_n \xrightarrow{\sim} Du$  in the space of measures on [-1,1]. Let us consider a weighted Lebesgue space  $L^2_{\mu}(\Omega) := \{v; \int_{\Omega} \mu |v|^2 \, \mathrm{d}x < +\infty\}$  with  $\mu \in L^1(\Omega)$  fixed; this is a Hilbert space which we identify standardly with its dual. Replacing both  $L^1(\Omega)$  and  $L^{\infty}(\Omega)$ in (2.18) by  $L^2_{\mu}(\Omega)$  shows that  $\{\frac{\mathrm{d}}{\mathrm{d}x}u_n\}_{n\in\mathbb{N}}$  is bounded also in  $L^2_{\mu}(\Omega)$  if the weight  $\mu$  is taken  $1/\zeta$ . Note that such  $\mu$  is absolutely continuous with respect to the Lebesgue measure. Hence the subsequence  $\{\frac{\mathrm{d}}{\mathrm{d}x}u_n\}_{n\in\mathbb{N}}$  converges also in  $L^2_{\mu}(\Omega)$ , hence  $Du \in L^2_{\mu}(\Omega)$ . In particular, Du is absolutely continuous with respect to  $\mu$ , and thus also with respect to the Lebesgue measure. This, however, shows that

$$g_0(\zeta) := \inf_{u \in W^{1,2}(\Omega; \mathbb{R}^d)} G_0(u,\zeta) = \lim_{n \to \infty} G_0(u_n,\zeta), = G_0(u,\zeta) > 0$$
(2.19)

because  $G_0(u, \zeta) = 0$  would be possible only for u constant on (-1, 0) (being equal to -1) and on (0, 1) (being equal to 1). Yet, such u has its gradient  $2\delta_0$ , with  $\delta_0$  denoting the Dirac measure at 0, which is not absolutely continuous.

**Corollary 2.3** For the scalar situation and  $\Omega$ ,  $\varphi$ , and  $\zeta$  from the above example, it holds  $\mathfrak{g}(\zeta) < \inf_{u \in W^{1,2}(\Omega; \mathbb{R}^d)} G_0(u, \zeta)$ .

*Proof.* Just use (2.17) and (2.19).

In fact, the above Corollary 2.3 just gives the counterexample for the (thus wrong) conjecture in [27, Remark 4.1].

#### 2.3 Realizable strain, stress and energy

The important question is the behavior of the stress

$$\sigma_{\varepsilon} = (\zeta_{\varepsilon} + \varepsilon)\varphi'_{e}(e(u_{\varepsilon})) = (\zeta_{\varepsilon} + \varepsilon)\mathbb{C}e(u_{\varepsilon}), \qquad (2.20)$$

where  $u_{\varepsilon}$  is the minimizer of  $G_{\varepsilon}(\cdot, \zeta_{\varepsilon})$  as well as the corresponding strain  $e(u_{\varepsilon})$  and the energy  $G_{\varepsilon}(\cdot, \zeta_{\varepsilon})$  itself, when  $\zeta_{\varepsilon}$  approaches  $\zeta$  weakly in  $W^{1,r}(\Omega)$  and  $\varepsilon \to 0+$ . We will denote such sort of limit objects by the adjective "realizable". For this, let us first define (possibly nonuniquely) a *realizable strain*  $\mathfrak{e}$ . Let us define standardly

$$L^{2}_{\text{loc}}(\Omega \setminus N_{\zeta}; \mathbb{R}^{d}) := \left\{ u : \Omega \setminus N_{\zeta} \to \mathbb{R}^{d}; \ \forall A \subset \Omega \setminus N_{\zeta} \text{ open}, \\ \operatorname{cl}(A) \cap N_{\zeta} = \emptyset : \quad u|_{A} \in L^{2}(A; \mathbb{R}^{d}) \right\}.$$
(2.21)

**Lemma 2.4** (*Realizable strains.*) The sequence  $\{e(u_{\varepsilon})\}_{\varepsilon>0}$  is bounded in  $L^2_{\text{loc}}(\Omega \setminus N_{\zeta}; \mathbb{R}^{d \times d}_{\text{sym}})$  and there is  $\mathbf{e} \in L^2_{\text{loc}}(\Omega \setminus N_{\zeta}; \mathbb{R}^{d \times d}_{\text{sym}})$  and a subsequence such that  $e(u_{\varepsilon}) \rightharpoonup \mathbf{e}$  weakly in  $L^2_{\text{loc}}(\Omega \setminus N_{\zeta}; \mathbb{R}^{d \times d}_{\text{sym}})$ , i.e.  $e(u_{\varepsilon})|_A \rightharpoonup \mathbf{e}|_A$  weakly in  $L^2(A; \mathbb{R}^{d \times d}_{\text{sym}})$  for any  $A \subset \Omega \setminus N_{\zeta}$  as in (2.21).

Proof. Let  $N_{\zeta} \neq \Omega$ , otherwise the statement is trivial. Without loss of generality, we can assume A's in (2.21) to be organized into an increasing sequence whose union is just  $\Omega \setminus N_{\zeta}$ . As  $\zeta_{\varepsilon} \to \zeta$  in  $C(\overline{\Omega})$ , for any  $A_j$  from this sequence there is  $\delta_{A_j} > 0$  and  $\varepsilon_0 > 0$  such that  $\zeta_{\varepsilon} + \varepsilon \geq \delta_{A_j}$  provided  $\varepsilon \leq \varepsilon_0$ . Then, for  $\varepsilon \leq \varepsilon_0$ ,

$$\int_{A_j} \varphi(e(u_{\varepsilon})) \, \mathrm{d}x \leq \frac{1}{\delta_{A_j}} \int_{A_j} (\zeta_{\varepsilon} + \varepsilon) \varphi(e(u_{\varepsilon})) \, \mathrm{d}x$$
$$\leq \frac{1}{\delta_{A_j}} \int_{\Omega} (\zeta_{\varepsilon} + \varepsilon) \varphi(e(u_{\varepsilon})) \, \mathrm{d}x = \frac{G_{\varepsilon}(u_{\varepsilon}, \zeta_{\varepsilon})}{\delta_{A_j}}, \qquad (2.22)$$

which is bounded uniformly with respect to  $\varepsilon > 0$ . By the assumed coercivity of  $\varphi$ , we have  $e(u_{\varepsilon})$  bounded in  $L^2(A_j; \mathbb{R}^{d \times d}_{sym})$ . Then we can select a subsequence of  $\varepsilon$ 's such that  $\{e(u_{\varepsilon})|_{A_j}\}$  converges weakly in  $L^2(A_j; \mathbb{R}^{d \times d}_{sym})$  if  $\varepsilon \to 0$  to some limit, let us denote it by  $\mathfrak{e}_{A_j}$ . Then we can take  $A_{j+1}$  and select further subsequence from this already selected one. This will keep the convergence of  $\{e(u_{\varepsilon})|_{A_j}\}$  and gives some  $\mathfrak{e}_{A_{j+1}}$  as a weak limit of the sub-subsequence  $\{e(u_{\varepsilon})|_{A_{j+1}}\}$ . Of course,  $\mathfrak{e}_{A_{j+1}}|_{A_j} = \mathfrak{e}_{A_j}$ . Inflating  $A_j$ 's by passing  $j \to \infty$  gives by the diagonalization procedure a subsequence of  $\{e(u_{\varepsilon})\}_{\varepsilon>0}$  and  $\mathfrak{e}$  defined a.e. on  $\Omega \setminus N_{\zeta}$  by  $\mathfrak{e}|_{A_j} := \mathfrak{e}_{A_j}$  with the claimed properties.  $\Box$ 

The following assertion introduces and characterizes a *realizable stress*  $\mathfrak{s}$  provided  $\mathfrak{e}$  is constructed by Lemma 2.4.

**Proposition 2.5** (Realizable stress.) The sequence  $\{\sigma_{\varepsilon}\}_{\varepsilon>0}$  is bounded in  $L^2(\Omega; \mathbb{R}^{d \times d}_{sym})$ , and each subsequence selected in Lemma 2.4 converges weakly to a realizable stress  $\mathfrak{s}$  that satisfies

$$\mathfrak{s} = \begin{cases} \zeta \varphi'_e(\mathfrak{e}) & on \ \Omega \backslash N_{\zeta}, \\ 0 & on \ N_{\zeta}. \end{cases}$$
(2.23)

Moreover, this convergence is even strong on  $N_{\zeta}$ .

*Proof.* It has already been observed in [27, Formula (4.11)] that  $\{\sigma_{\varepsilon}\}_{\varepsilon>0}$  is bounded in  $L^2(\Omega; \mathbb{R}^{d \times d}_{sym})$ . Indeed, using the property of the quadratic form  $\varphi$ 

$$\exists C_{\varphi} < +\infty \quad \forall e \in \mathbb{R}^{d \times d}_{\text{sym}} : \qquad |\varphi'_{e}(e)|^{2} = \varphi'_{e}(e) : \varphi'_{e}(e) \le C_{\varphi}\varphi(e), \ (2.24)$$

we obtain

$$\begin{split} \limsup_{\varepsilon \to 0} \left\| \sigma_{\varepsilon} \right\|_{L^{2}(\Omega; \mathbb{R}^{d \times d}_{sym})}^{2} &= \limsup_{\varepsilon \to 0} \int_{\Omega} (\zeta_{\varepsilon} + \varepsilon)^{2} |\varphi'_{e}(e(u_{\varepsilon}))|^{2} \, dx \\ &\leq \limsup_{\varepsilon \to 0} \left( \| \zeta_{\varepsilon} \|_{L^{\infty}(\Omega)} + \varepsilon \right) \int_{\Omega} (\zeta_{\varepsilon} + \varepsilon) |\varphi'_{e}(e(u_{\varepsilon}))|^{2} \, dx \\ &\leq \limsup_{\varepsilon \to 0} \left( \| \zeta_{\varepsilon} \|_{L^{\infty}(\Omega)} + \varepsilon \right) C_{\varphi} \int_{\Omega} (\zeta_{\varepsilon} + \varepsilon) \varphi(e(u_{\varepsilon})) \, dx \\ &= \| \zeta \|_{L^{\infty}(\Omega)} C_{\varphi} \limsup_{\varepsilon \to 0} \int_{\Omega} (\zeta_{\varepsilon} + \varepsilon) \varphi(e(u_{\varepsilon})) \, dx < +\infty. \end{split}$$
(2.25)

Hence we can consider a subsequence and a limit realizable stress  $\mathfrak{s}$  such that  $\sigma_{\varepsilon} \rightharpoonup \mathfrak{s}$  in  $L^2(\Omega; \mathbb{R}^{d \times d}_{svm})$ .

Having  $\zeta_{\varepsilon} \to \zeta$  weakly in  $W^{1,r}(\Omega)$ , hence strongly in  $L^{\infty}(\Omega)$ , and  $e(u_{\varepsilon})|_A \rightharpoonup \mathfrak{e}|_A$ (a subsequence) in  $L^2(A; \mathbb{R}^{d \times d}_{sym})$  for each A as in (2.21), we can just pass to the limit in (2.20) to get the equality  $\mathfrak{s} = \zeta \varphi'_e(\mathfrak{e})$  on A. For this, we used that  $\varphi'_e$  in (2.20) is linear. Inflating A yields this equality on the whole  $\Omega \setminus N_{\zeta}$  in the sense of  $L^2_{loc}(\Omega \setminus N_{\zeta}; \mathbb{R}^{d \times d}_{sym})$  and thus also  $L^2(\Omega \setminus N_{\zeta}; \mathbb{R}^{d \times d}_{sym})$  because  $\mathfrak{s} \in L^2(\Omega; \mathbb{R}^{d \times d}_{sym})$ . On the other hand,  $\mathfrak{s} = 0$  on  $N_{\zeta}$  because  $\zeta_{\varepsilon} \to 0$  in  $L^{\infty}(N_{\zeta})$  and, similarly as in (2.25), we can estimate

$$\left\|\sigma_{\varepsilon}\right\|_{L^{2}(N_{\zeta};\mathbb{R}^{d\times d}_{\text{sym}})}^{2} \leq \underbrace{\left(\sup_{N_{\zeta}}\zeta_{\varepsilon}+\varepsilon\right)}_{\text{converges to }0} C_{\varphi}\underbrace{\int_{N_{\zeta}}(\zeta_{\varepsilon}+\varepsilon)\varphi(e(u_{\varepsilon}))\,\mathrm{d}x}_{\text{remains bounded}} \stackrel{\text{for }\varepsilon\to0}{\longrightarrow} 0.$$
(2.26)

Hence we have the complete formula (2.23) for the realizable stress. As we identified the limit by means of  $\mathfrak{e}$  constructed by a subsequence selected for Lemma 2.4, we do not need to select a further subsequence here.

In view of (2.4), we obtained

$$\mathfrak{s}_{ij} = \begin{cases} \zeta \sum_{k,l=1}^{d} \mathbb{C}_{ijkl} \mathfrak{e}_{kl} & \text{on } \Omega \backslash N_{\zeta}, \\ 0 & \text{on } N_{\zeta}. \end{cases}$$
(2.27)

The further important quantity is the realizable energy density  $\mathfrak{E}$  describing the limit behavior of the specific stored energy  $E_{\varepsilon} := (\zeta_{\varepsilon} + \varepsilon)\varphi(e(u_{\varepsilon}))$  related to the unique minimizer  $u_{\varepsilon}$  of the regularized problem  $G_{\varepsilon}(\cdot, \zeta_{\varepsilon})$ . Let us also note that  $u_{\varepsilon}$  is the minimizer of  $G_{\varepsilon}(\cdot, \zeta_{\varepsilon})$  satisfies the Euler-Lagrange equation, i.e. in the weak form,

$$\forall v \in W^{1,2}(\Omega; \mathbb{R}^d), \ v|_{\Gamma} = 0: \qquad \int_{\Omega} (\zeta_{\varepsilon} + \varepsilon) \varphi'_e(e(u_{\varepsilon})) : e(v) \ \mathrm{d}x = 0.$$
(2.28)

Considering  $u_{\rm D}$  is a continuation of the Dirichlet boundary data w onto  $\Omega$ , using  $v = u_{\varepsilon} - u_{\rm D}$  in (2.28) and realizing also (2.4) and (2.20) then yield the formula for the total energy

$$\int_{\Omega} E_{\varepsilon}(x) \, \mathrm{d}x = \int_{\Omega} (\zeta_{\varepsilon} + \varepsilon) \varphi(e(u_{\varepsilon})) \, \mathrm{d}x$$
$$= \frac{1}{2} \int_{\Omega} (\zeta_{\varepsilon} + \varepsilon) \varphi'_{e}(e(u_{\varepsilon})) : e(u_{\varepsilon}) \, \mathrm{d}x$$
$$= \frac{1}{2} \int_{\Omega} (\zeta_{\varepsilon} + \varepsilon) \varphi'_{e}(e(u_{\varepsilon})) : e(u_{\mathrm{D}}) \, \mathrm{d}x = \frac{1}{2} \int_{\Omega} \sigma_{\varepsilon} : e(u_{\mathrm{D}}) \, \mathrm{d}x. \quad (2.29)$$

**Proposition 2.6** (Realizable energy.) The sequence  $\{E_{\varepsilon}\}_{\varepsilon>0}$  is bounded in  $L^1(\Omega)$ , and thus, as a subsequence, converges weakly\* to a realizable energy density, let us denote it by  $\mathfrak{E}$ . This density is a measure on  $\overline{\Omega}$  such that  $\lim_{\varepsilon\to 0} G_{\varepsilon}(u_{\varepsilon}, \zeta_{\varepsilon}) = \lim_{\varepsilon\to 0} \int_{\Omega} E_{\varepsilon}(x) dx = \int_{\overline{\Omega}} \mathfrak{E}(dx)$ . In particular, it holds for the subsequence selected already in Lemma 2.4 and then, for  $\mathfrak{e}$  from Lemma 2.4 and  $\mathfrak{s}$  from (2.27), it holds

$$\int_{\bar{\Omega}} \mathfrak{E}(\mathrm{d}x) = \frac{1}{2} \int_{\Omega} \mathfrak{s} : e(u_{\mathrm{D}}) \, \mathrm{d}x = \int_{\Omega \setminus N_{\zeta}} \zeta \sum_{k,l=1}^{d} \mathbb{C}_{ijkl} \mathfrak{e}_{kl} : e(u_{\mathrm{D}}) \, \mathrm{d}x, \tag{2.30}$$

where  $u_{\mathrm{D}} \in W^{1,2}(\Omega; \mathbb{R}^d)$  is an (arbitrary) continuation of w onto  $\Omega$ .

*Proof.* It just suffices to apply Proposition 2.5 to (2.29) and apply (2.27).

**Example 2.7** (Nonuniqueness of  $\mathfrak{e}, \mathfrak{s}, and \mathfrak{E}$ .) Referring to Section 2.2, we consider  $\zeta_{\varepsilon} := \zeta_n$  from (2.15) with  $n = n(\varepsilon)$  such that  $n \to \infty$  but  $\varepsilon n(\varepsilon)^{1/\alpha} \to 0$  for  $\varepsilon \to 0$ . Then, for  $\varepsilon$  small,  $\zeta_{\varepsilon} + \varepsilon$  and the corresponding  $u_{\varepsilon}$  essentially approach the profiles  $\zeta_{n(\varepsilon)}$  and  $u_{n(\varepsilon)}$  from (2.15) and (2.16), respectively. This is because the overall stiffness of the slot of the length  $2n(\varepsilon)^{-1/\alpha}$  filled of "material" with the elastic modulus  $\varepsilon$  is  $\frac{1}{2}\varepsilon n(\varepsilon)^{1/\alpha}$  and asymptotically goes to zero so that asymptotically we approach the situation in Section 2.2. For this  $u_{n(\varepsilon)}$ , we have got  $e(u_{n(\varepsilon)}) = 0$  on  $\Omega \setminus \{-\frac{1}{n(\varepsilon)}, \frac{1}{n(\varepsilon)}\}$ . For  $\zeta_{\varepsilon} + \varepsilon$ , this holds only asymptotically but, nevertheless, the limit is the same, namely  $\mathfrak{e} = 0$  on  $\Omega \setminus \{0\}$ . Also the corresponding stress and the energy is (asymptotically) zero, and thus in the limit both  $\mathfrak{s}$  and  $\mathfrak{E}$  are zero. On the other hand, for  $\zeta_{\varepsilon} := \zeta$  from (2.14), the displacement profile  $u_{\varepsilon} \in W^{1,2}(\Omega)$  corresponding to  $\zeta_{\varepsilon} + \varepsilon$  essentially imitates (2.19), i.e.  $G_0(u_{\varepsilon}, \zeta_{\varepsilon} + \varepsilon)$  converges to  $G_0(u, \zeta) > 0$  constructed in Section 2.2. In particular,  $\mathfrak{e} = e(u) \neq 0$ ,  $\mathfrak{s} = \zeta e(u) \neq 0$ , and also  $\int_{[-1,1]} \mathfrak{E}(dx) > 0$ . Of course, in both cases  $\zeta_{\varepsilon} + \varepsilon$  converges to the same limit profile  $\zeta$ .

In view of the above Example 2.7, it makes sense to consider the set of all realizable stresses  $\mathfrak{s}$  for a given damage profile:

$$\mathfrak{S}(\zeta) := \left\{ \mathfrak{s} \in L^2(\Omega; \mathbb{R}^{d \times d}_{\text{sym}}); \quad \exists \zeta_{\varepsilon} \rightharpoonup \zeta \text{ weakly in } W^{1,r}(\Omega) : \\ \sigma_{\varepsilon} \rightharpoonup \mathfrak{s} \text{ weakly in } L^2(\Omega; \mathbb{R}^{d \times d}_{\text{sym}}) \text{ with } \sigma_{\varepsilon} \text{ from } (2.20) \right\}.$$
(2.31)

#### **Proposition 2.8** The set $\mathfrak{S}(\zeta)$ is weakly compact in $L^2(\Omega; \mathbb{R}^{d \times d}_{sym})$ .

Proof. By arguments like in the proof of Proposition 2.5, we can see that the set  $\mathfrak{S}(\zeta)$  is bounded in  $L^2(\Omega; \mathbb{R}^{d \times d}_{sym})$ ; in fact, all its elements must share the bound in (2.25). Due to metrizability of the weak topology on bounded sets of  $L^2(\Omega; \mathbb{R}^{d \times d}_{sym})$ , we can equally focus on sequential compactness. Take a sequence  $\{\mathfrak{s}_j\}_{j \in \mathbb{N}} \subset \mathfrak{S}(\zeta)$ . As it is bounded in  $L^2(\Omega; \mathbb{R}^{d \times d}_{sym})$ , it contains a subsequence (for simplicity denoted by the same indexes) converging weakly in  $L^2(\Omega; \mathbb{R}^{d \times d}_{sym})$ ; let  $\mathfrak{s}$  denote its limit. As  $\mathfrak{s}_j \in \mathfrak{S}(\zeta)$  for each j, there are sequences  $\{\zeta_{\varepsilon_{jk}}\}_{k \in \mathbb{N}}$  such that  $\lim_{k \to \infty} \varepsilon_{jk} = 0$ , w- $\lim_{k \to \infty} \zeta_{\varepsilon_{jk}} = \zeta_j$  (meant weakly in  $W^{1,r}(\Omega)$ ) and w- $\lim_{k \to \infty} \sigma_{\varepsilon_{jk}} = \mathfrak{s}_j$  with  $\sigma_{\varepsilon_{jk}} = (\zeta_{\varepsilon_{jk}} + \varepsilon_{jk})\varphi'_e(e(u_{\varepsilon_{jk}}))$ . By the diagonalization procedure we obtain a sequence  $\{\sigma_{\varepsilon_{jnkn}}\}_{n \in \mathbb{N}}$  converging to  $\mathfrak{s}$ , which shows that  $\mathfrak{s} \in \mathfrak{S}(\zeta)$ .

#### Proposition 2.9 It holds

$$\mathfrak{g}(\zeta) = \min_{\mathfrak{s}\in\mathfrak{S}(\zeta)} \frac{1}{2} \int_{\Omega} \mathfrak{s} : e(u_{\mathrm{D}}) \, \mathrm{d}x \tag{2.32}$$

where  $u_{\mathrm{D}} \in W^{1,2}(\Omega; \mathbb{R}^d)$  is as in Proposition 2.6.

*Proof.* As  $u_{\text{D}} \in W^{1,2}(\Omega; \mathbb{R}^d)$ , also  $e(u_{\text{D}}) \in L^2(\Omega; \mathbb{R}^{d \times d}_{\text{sym}})$ , and  $\mathfrak{s} \mapsto \frac{1}{2} \int_{\Omega} \mathfrak{s} : e(u_{\text{D}}) dx$  is a weakly continuous functional which obviously attains its minimum on the set  $\mathfrak{S}(\zeta)$  which is, due to Proposition 2.8, weakly compact.

By the definition (2.10) of  $\mathfrak{g}$ , the sequence  $(\varepsilon, \tilde{\zeta}) \to (0, \zeta)$  infinizing the expression in (2.10) gives a cluster point  $\mathfrak{s}$  of the corresponding sequence  $\{\sigma_{\varepsilon,\tilde{\zeta}}\}$  with  $\sigma_{\varepsilon,\tilde{\zeta}} = (\tilde{\zeta} + \varepsilon)\varphi'_e(e(u_{\varepsilon,\tilde{\zeta}}))$  where  $\sigma_{\varepsilon,\tilde{\zeta}}$  minimizes  $G_{\varepsilon}(\cdot, \tilde{\zeta})$ , cf. (2.20). This yields  $\mathfrak{s} \in \mathfrak{S}(\zeta)$  and, using also (2.29),

$$\mathfrak{g}(\zeta) = \lim_{(\varepsilon,\tilde{\zeta})\to(0,\zeta)} \int_{\Omega} (\tilde{\zeta} + \varepsilon) \varphi(e(u_{\varepsilon,\tilde{\zeta}})) \, \mathrm{d}x = \lim_{(\varepsilon,\tilde{\zeta})\to(0,\zeta)} \frac{1}{2} \int_{\Omega} \sigma_{\varepsilon,\tilde{\zeta}} : e(u_{\mathrm{D}}) \, \mathrm{d}x$$
$$= \frac{1}{2} \int_{\Omega} \mathfrak{s} : e(u_{\mathrm{D}}) \, \mathrm{d}x \ge \min_{\tilde{\mathfrak{s}}\in\mathfrak{S}(\zeta)} \frac{1}{2} \int_{\Omega} \widetilde{\mathfrak{s}} : e(u_{\mathrm{D}}) \, \mathrm{d}x.$$
(2.33)

Conversely, taking  $\mathfrak{s} \in \mathfrak{S}(\zeta)$  at which the minimum in (2.32) is attained and, by (2.31), the sequence  $\{\zeta_{\varepsilon}\}_{\varepsilon>0}$  such that the corresponding  $\{\sigma_{\varepsilon}\}_{\varepsilon>0}$  attains  $\mathfrak{s}$ , using again also (2.29), we obtain

$$\begin{split} \mathfrak{g}(\zeta) &\leq \liminf_{\varepsilon \to 0} \int_{\Omega} (\zeta_{\varepsilon} + \varepsilon) \varphi(e(u_{\varepsilon})) \, \mathrm{d}x = \lim_{\varepsilon \to 0} \frac{1}{2} \int_{\Omega} \sigma_{\varepsilon} : e(u_{\mathrm{D}}) \, \mathrm{d}x \\ &= \frac{1}{2} \int_{\Omega} \mathfrak{s} : e(u_{\mathrm{D}}) \, \mathrm{d}x = \min_{\widetilde{\mathfrak{s}} \in \mathfrak{S}(\zeta)} \frac{1}{2} \int_{\Omega} \widetilde{\mathfrak{s}} : e(u_{\mathrm{D}}) \, \mathrm{d}x. \end{split}$$

Let us note that the formula (2.32) determines (still nonuniquely) a stress  $\mathfrak{s}$  that realizes the minimum in (2.32). Let us call it a *minimizing realizable stress*. Naturally, we can think also about the corresponding *minimizing realizable strain* 

 $\mathfrak{e} \in L^2_{\mathrm{loc}}(\Omega \setminus N_{\zeta}; \mathbb{R}^{d \times d}_{\mathrm{sym}})$  related with  $\mathfrak{s}$  by

$$\mathbf{\mathfrak{e}}(x) = \left[\varphi'_e\right]^{-1} \left(\frac{\mathbf{\mathfrak{s}}(x)}{\zeta(x)}\right) \quad \text{for a.a. } x \in \Omega \backslash N_{\zeta}. \tag{2.34}$$

Let us agree to call the realizable stress  $\mathfrak{s} \in \mathfrak{S}(\zeta)$  which realizes the minimum in (2.32) an *effective stress* and  $\mathfrak{e}$  corresponding to it via (2.34) the *effective strain*.

## 2.4 Effective stress and strain, and sensitivity to the boundary data

Now, we construct a particular effective stress, i.e. a minimizer for (2.32), that provides a characterization of the  $\Gamma$ -limit (2.11)–(2.12) as a pointwise limit and it leads to a selection of a particular effective stress and that this effective stress can be recovered by using a particular approximating sequence  $\zeta_{\varepsilon}$ . Thus we will be able to prove a specific differentiable behavior (sometimes, in optimization theory, called a *sensitivity*) of this  $\Gamma$ -limit with respect to varying boundary conditions.

For this, we apply the standard shift of the Dirichlet condition. Let us abbreviate the linear space  $W^{1,2}_{\Gamma}(\Omega; \mathbb{R}^d) := \{ v \in W^{1,2}(\Omega; \mathbb{R}^d); v |_{\Gamma} = 0 \}$ . Considering  $e_{\mathrm{D}} \in L^2(\Omega; \mathbb{R}^{d \times d}_{\mathrm{sym}})$ , we define

$$F_{\varepsilon}(e_{\mathrm{D}}, v, \zeta) := \int_{\Omega} (\zeta + \varepsilon) \varphi \left( x, e_{\mathrm{D}} + e(v) \right) \, \mathrm{d}x.$$
(2.35)

Note that, considering again the continuation  $u_{\rm D}$  of the Dirichlet condition w as in Proposition 2.6 and  $G_{\varepsilon}$  from (2.9), we have

$$G_{\varepsilon}(u,\zeta) = F_{\varepsilon}(e_{\rm D}, v,\zeta) \quad \text{with } e_{\rm D} := e(u_{\rm D}) \quad \text{and} \quad v := u - u_{\rm D}, \tag{2.36}$$

for any  $v \in W^{1,2}_{\Gamma}(\Omega; \mathbb{R}^d)$  or, equally, for any  $u \in W^{1,2}(\Omega; \mathbb{R}^d)$  such that  $u|_{\Gamma} = w$ . For  $e_{\scriptscriptstyle D} \in L^2(\Omega; \mathbb{R}^{d \times d}_{sym})$  let

$$f_{\varepsilon}(e_{\mathrm{D}},\zeta) := \min_{v \in W_{\Gamma}^{1,2}(\Omega;\mathbb{R}^d)} F_{\varepsilon}(e_{\mathrm{D}},v,\zeta).$$
(2.37)

For  $\varepsilon > 0$ , the strictly convex quadratic functional  $F_{\varepsilon}(e_{\mathrm{D}}, \cdot, \zeta)$  on  $W^{1,2}_{\Gamma}(\Omega; \mathbb{R}^d)$  has a unique minimizer, say v, and the mapping  $L_{\zeta+\varepsilon}$  defined as

$$e_{\mathrm{D}} \mapsto L_{\zeta + \varepsilon} v : L^2(\Omega; \mathbb{R}^{d \times d}_{\mathrm{sym}}) \to W^{1,2}_{\Gamma}(\Omega; \mathbb{R}^d), \quad v \text{ minimizes } F_{\varepsilon}(e_{\mathrm{D}}, \cdot, \zeta), \quad (2.38)$$

is linear and bounded. Hence, we conclude that, for each  $\zeta$ , the functional

$$e_{\rm D} \mapsto f_{\varepsilon}(e_{\rm D},\zeta) = F_{\varepsilon}(e_{\rm D}, L_{\zeta+\varepsilon}e_{\rm D},\zeta) \tag{2.39}$$

is a quadratic form on  $L^2(\Omega; \mathbb{R}^{d \times d}_{\text{sym}})$  which, moreover, is bounded uniformly, namely  $0 \leq f_{\varepsilon}(e_{\text{D}}, \zeta) \leq C \|e_{\text{D}}\|^2_{L^2(\Omega; \mathbb{R}^{d \times d}_{\text{sym}})}$  with  $C := (\|\zeta\|_{C(\bar{\Omega})} + \varepsilon) \|\mathbb{C}\|_{L^{\infty}(\Omega; \mathbb{R}^{d \times d \times d \times d})}$ .

Now, like in (2.10), we consider the  $\Gamma$ -limit of the collection  $\{f_{\varepsilon}(\cdot,\zeta)\}_{\varepsilon>0,\zeta\in\mathbb{Z}}$  as

$$\mathfrak{f}(e_{\scriptscriptstyle \mathrm{D}},\zeta) := \liminf_{\substack{\varepsilon \to 0+\\ \tilde{\zeta} \to \zeta, \ \tilde{\zeta} \in Z}} f_{\varepsilon}(e_{\scriptscriptstyle \mathrm{D}},\tilde{\zeta}) \tag{2.40}$$

with Z defined in (2.1). The following assertion is based on an explicit construction to a universal recovery sequence for the  $\Gamma$ -limit (2.40).

**Proposition 2.10** (A formula for the  $\Gamma$ -limit  $\mathfrak{f}$ .) For all  $\zeta \in Z$  the functional  $\mathfrak{f}(\cdot, \zeta) : L^2(\Omega; \mathbb{R}^{d \times d}_{sym}) \to \mathbb{R}$  is convex and quadratic, and can be obtained as follows:

$$\mathfrak{f}(e_{\mathrm{D}},\zeta) = \lim_{\delta \to 0+} \left( \lim_{\varepsilon \to 0+} \mathcal{F}(\varepsilon,\delta,e_{\mathrm{D}},\zeta) \right),\tag{2.41}$$

where

$$\mathcal{F}(\varepsilon,\delta,e_{\mathrm{D}},\zeta) = f_{\varepsilon}(e_{\mathrm{D}},(\zeta-\delta)^{+}) \quad with \ (\zeta-\delta)^{+} := \max\{\zeta-\delta,0\}.$$
(2.42)

*Proof.* Note that each  $\mathcal{F}(\varepsilon, \delta, \cdot, \zeta)$  is a bounded convex quadratic form on  $L^2(\Omega; \mathbb{R}^{d \times d}_{sym})$ . If the limit exists, then it will be a convex quadratic form again.

For the existence of the limits, we use the following monotonicities of  $\mathcal{F}$ :

$$0 < \varepsilon_1 < \varepsilon_2 \quad \Longrightarrow \quad \mathcal{F}(\varepsilon_1, \delta, e_{\mathrm{D}}, \zeta) < \mathcal{F}(\varepsilon_2, \delta, e_{\mathrm{D}}, \zeta); \tag{2.43a}$$

$$0 < \delta_1 < \delta_2 \quad \Longrightarrow \quad \mathcal{F}(\varepsilon, \delta_1, e_{\mathrm{D}}, \zeta) \ge \mathcal{F}(\varepsilon, \delta_2, e_{\mathrm{D}}, \zeta). \tag{2.43b}$$

This follows easily from the monotonicity  $F_{\varepsilon_1}(e_{\mathrm{D}}, v, \zeta_1) \leq F_{\varepsilon_2}(e_{\mathrm{D}}, v, \zeta_2)$ , and hence also  $f_{\varepsilon_1}(e_{\mathrm{D}}, \zeta_1) \leq f_{\varepsilon_2}(e_{\mathrm{D}}, \zeta_2)$ , whenever  $0 < \varepsilon_1 + \zeta_1 \leq \varepsilon_2 + \zeta_2$ .

Thus, the existence of the inner limit  $\varepsilon \to 0+$  follows because the function is nonincreasing in  $\varepsilon$ , let us denote it as  $\mathcal{F}_0(\delta, e_{\mathrm{D}}, \zeta) := \lim_{\varepsilon \to 0+} \mathcal{F}(\varepsilon, \delta, e_{\mathrm{D}}, \zeta)$ , Hence,  $\mathcal{F}_0(\delta, \cdot, \zeta)$  exists and is a bounded quadratic form on  $L^2(\Omega; \mathbb{R}^{d \times d}_{\mathrm{sym}})$ . Moreover,  $\mathcal{F}_0(\cdot, u_{\mathrm{D}}, \zeta)$  is still non-decreasing on [0, 1]. Hence,  $\mathcal{F}_{00}(e_{\mathrm{D}}, \zeta) := \lim_{\delta \to 0+} \mathcal{F}_0(\delta, u_{\mathrm{D}}, \zeta)$ exists and for each  $\zeta \in Z$ , the functional  $\mathcal{F}_{00}(\cdot, \zeta) : L^2(\Omega; \mathbb{R}^{d \times d}_{\mathrm{sym}}) \to \mathbb{R}$  is a bounded quadratic form.

As  $\mathcal{F}_{00}(u_{\rm D},\zeta)$  is just the right-hand side of (2.41), it remains to show that  $\mathfrak{f}=\mathcal{F}_{00}$ .

To show  $\mathfrak{f} \geq \mathcal{F}_{00}$ , we take a recovery sequence  $\zeta_{\varepsilon}$  for (2.40), i.e. such that  $\zeta_{\varepsilon} \rightharpoonup \zeta$ ,  $\zeta_{\varepsilon} \geq 0$ , and  $f_{\varepsilon}(e_{\mathrm{D}}, \zeta_{\varepsilon}) \rightarrow \mathfrak{f}(e_{\mathrm{D}}, \zeta)$ . For each  $\delta > 0$  there exists  $\varepsilon_{\delta} > 0$  such that  $\zeta_{\varepsilon} \geq (\zeta - \delta)^+$  for  $\varepsilon \in (0, \varepsilon_{\delta})$ ; note that here r > d was essential. Hence, we find  $f_{\varepsilon}(e_{\mathrm{D}}, \zeta_{\varepsilon}) \geq \mathcal{F}(\varepsilon, \delta, e_{\mathrm{D}}, \zeta)$ . Keeping  $\delta > 0$  fixed and letting  $\varepsilon \rightarrow 0+$  we find  $\mathfrak{g}(e_{\mathrm{D}}, \zeta) \geq \mathcal{F}_{0}(\delta, e_{\mathrm{D}}, \zeta)$ . Now taking the limit  $\delta \rightarrow 0+$  we obtain  $\mathfrak{f}(e_{\mathrm{D}}, \zeta) \geq \mathcal{F}_{00}(e_{\mathrm{D}}, \zeta)$ .

To show  $\mathfrak{f} \leq \mathcal{F}_{00}$ , we use a diagonalization argument to find a sequence  $0 < \delta_{\varepsilon} \to 0$ for  $\varepsilon \to 0+$  such that  $\mathcal{F}(\varepsilon, \delta_{\varepsilon}, e_{\mathrm{D}}, \zeta) \to \mathcal{F}_{00}(e_{\mathrm{D}}, \zeta)$ . Now consider the functions  $\zeta_{\varepsilon} = (\zeta - \delta_{\varepsilon})^+$ , so that  $\mathcal{F}(\varepsilon, \delta_{\varepsilon}, e_{\mathrm{D}}, \zeta) = f_{\varepsilon}(e_{\mathrm{D}}, \zeta_{\varepsilon})$ . Because of  $\delta_{\varepsilon} \to 0$  we easily find that  $\zeta_{\varepsilon} \to \zeta$  in  $W^{1,r}(\Omega)$  because obviously  $\zeta_{\varepsilon} \to \zeta$  in  $C(\overline{\Omega})$  and because always  $|\nabla \zeta_{\varepsilon}| \leq |\nabla \zeta|$  a.e. on  $\Omega$ . Also,  $\zeta_{\varepsilon} \in Z$  because  $\zeta \in Z$  and  $\delta_{\varepsilon} \geq 0$ . Hence we conclude by the definition of the  $\Gamma$ -limit that

$$\mathfrak{f}(e_{\mathrm{D}},\zeta) \leq \liminf_{\varepsilon \to 0+} f_{\varepsilon}(e_{\mathrm{D}},\zeta_{\varepsilon}) = \lim_{\varepsilon \to 0+} \mathcal{F}(\varepsilon,\delta_{\varepsilon},e_{\mathrm{D}},\zeta) = \mathcal{F}_{00}(e_{\mathrm{D}},\zeta).$$
(2.44)

Let us now focus on sensitivity with respect to the boundary condition w or, more conveniently, to its extension  $u_{\rm D}$ . In the "language" of this subsection, it means rather sensitivity with respect to  $e_{\rm D}$ . As  $\mathfrak{f}(\cdot, \zeta)$  was proved to be a bounded quadratic form, its derivative is a bounded linear operator, let us denote it by  $\mathfrak{T}_{\zeta} : L^2(\Omega; \mathbb{R}^{d \times d}_{\rm sym}) \to L^2(\Omega; \mathbb{R}^{d \times d}_{\rm sym})$ . Thus we define a stress

$$\tau = \tau(e_{\mathrm{D}}, \zeta) := \mathfrak{T}_{\zeta} e_{\mathrm{D}} := \mathfrak{f}'_{e_{\mathrm{D}}}(e_{\mathrm{D}}, \zeta).$$

$$(2.45)$$

Let us now relate this to the original quantities as defined before. The following lemma uses an argument developed in [26, Proposition 5.6], which in turn is an abstract version of a result in [7].

**Lemma 2.11** Let  $\{\zeta_{\varepsilon}\}_{\varepsilon>0}$  be a recovery sequence for  $\mathfrak{f}(e_{\mathrm{D}}, \zeta)$  as defined by (2.40), let  $e_{\mathrm{D}} = e(u_{\mathrm{D}})$ , and let  $\sigma_{\varepsilon}$  be the stress corresponding to  $\zeta_{\varepsilon}$  and  $u_{\mathrm{D}}$  due to the formula (2.20). Then, referring to (2.45), it holds  $\sigma_{\varepsilon} \rightharpoonup \tau$  in  $L^2(\Omega; \mathbb{R}^{d \times d}_{\mathrm{sym}})$ .

*Proof.* In view of (2.40), having assumed  $\{\zeta_{\varepsilon}\}$  a recovery sequence, we just assume  $f_{\varepsilon}(e_{\mathrm{D}}, \zeta_{\varepsilon}) \to \mathfrak{f}(e_{\mathrm{D}}, \zeta), \varepsilon \to 0+$ , and  $\zeta_{\varepsilon} \rightharpoonup \zeta$ . For any other  $e \in L^{2}(\Omega; \mathbb{R}^{d \times d}_{\mathrm{sym}})$ , we have only

$$\liminf_{\varepsilon \to 0} f_{\varepsilon}(e, \zeta_{\varepsilon}) \ge \mathfrak{f}(e, \zeta) \tag{2.46}$$

just by the definition of the  $\Gamma$ -limit (2.40). Let us put  $\tau_{\varepsilon} := [f_{\varepsilon}]'_{e_{\mathrm{D}}}(e_{\mathrm{D}}, \zeta_{\varepsilon})$ . We want to show that  $\tau_{\varepsilon} \rightharpoonup \tau$  with  $\tau$  from (2.45). As  $\{\tau_{\varepsilon}\}_{\varepsilon>0}$  is bounded in  $L^2(\Omega; \mathbb{R}^{d\times d}_{\mathrm{sym}})$ , there is at least a subsequence converging to some  $\tilde{\tau}$  weakly. By the definition of  $\tau_{\varepsilon}$  and by the convexity of  $f_{\varepsilon}(\cdot, \zeta_{\varepsilon})$ , for any h > 0 and any  $e \in L^2(\Omega; \mathbb{R}^{d\times d}_{\mathrm{sym}})$ , we have

$$\int_{\Omega} \tau_{\varepsilon} : \tilde{e} \, \mathrm{d}x \le \frac{f_{\varepsilon}(e_{\mathrm{D}}, \zeta_{\varepsilon}) - f_{\varepsilon}(e_{\mathrm{D}} - h\tilde{e}, \zeta_{\varepsilon})}{h} \,. \tag{2.47}$$

Passing  $\varepsilon \to 0+$  in (2.47) and using (2.46) for  $e := e_{\rm D} - h\tilde{e}$ , we obtain

$$\int_{\Omega} \tilde{\tau} : \tilde{e} \, \mathrm{d}x = \lim_{\varepsilon \to 0+} \int_{\Omega} \tau_{\varepsilon} : \tilde{e} \, \mathrm{d}x \le \limsup_{\varepsilon \to 0+} \frac{f_{\varepsilon}(e_{\mathrm{D}}, \zeta_{\varepsilon}) - f_{\varepsilon}(e_{\mathrm{D}} - h\tilde{e}, \zeta_{\varepsilon})}{h}$$
$$= \frac{1}{h} \lim_{\varepsilon \to 0+} f_{\varepsilon}(e_{\mathrm{D}}, \zeta_{\varepsilon}) - \frac{1}{h} \liminf_{\varepsilon \to 0+} f_{\varepsilon}(e_{\mathrm{D}} - h\tilde{e}, \zeta_{\varepsilon}) \le \frac{\mathfrak{f}(e_{\mathrm{D}}, \zeta) - \mathfrak{f}(e_{\mathrm{D}} - h\tilde{e}, \zeta)}{h}. \quad (2.48)$$

Passing  $h \to 0+$  in (2.48), by (2.45) we obtain  $\int_{\Omega} \tilde{\tau} : \tilde{e} \, dx \leq \int_{\Omega} f'_{e_{\mathrm{D}}}(e_{\mathrm{D}}, \zeta) : \tilde{e} \, dx = \int_{\Omega} \tau : \tilde{e} \, dx$ . Making the same procedure with  $-\tilde{e}$  instead of  $\tilde{e}$ , we get also the

opposite inequality. Taking  $\tilde{e}$  arbitrary, we can see that that  $\tilde{\tau} = \tau$ . In particular, the whole sequence  $\{\tau_{\varepsilon}\}_{\varepsilon>0}$  converges to  $\tau$ .

Now it remains to show that  $\sigma_{\varepsilon} = \tau_{\varepsilon}$ . Referring to  $L_{\zeta+\varepsilon}$  from (2.38) and the definition of  $u_{\varepsilon}$  from (2.20) as a minimizer of  $G_{\varepsilon}(\cdot, \zeta_{\varepsilon})$ , by using the shift  $v_{\varepsilon} = u_{\varepsilon} - u_{\mathrm{D}}$  (cf. 2.36)) and  $v_{\varepsilon} := L_{\zeta_{\varepsilon}+\varepsilon} e(u_{\mathrm{D}})$ , we have  $u_{\varepsilon} = u_{\mathrm{D}} + L_{\zeta_{\varepsilon}+\varepsilon} e(u_{\mathrm{D}})$ . By (2.39) with (2.35), we have

$$f_{\varepsilon}(e_{\mathrm{D}},\zeta_{\varepsilon}) = F_{\varepsilon}(e_{\mathrm{D}},L_{\zeta_{\varepsilon}+\varepsilon}e(u_{\mathrm{D}}),\zeta_{\varepsilon}) = \int_{\Omega} (\zeta_{\varepsilon}+\varepsilon)\varphi(x,e_{\mathrm{D}}+e(L_{\zeta_{\varepsilon}+\varepsilon}e(u_{\mathrm{D}}))) \,\mathrm{d}x$$
$$= \int_{\Omega} (\zeta_{\varepsilon}+\varepsilon)\varphi(x,e_{\mathrm{D}}+e(u_{\varepsilon}-u_{\mathrm{D}})) \,\mathrm{d}x \,. \quad (2.49)$$

Differentiating both sides of (2.49) with respect to  $e_{\rm D}$ , we obtain

$$\tau_{\varepsilon} := [f_{\varepsilon}]'_{e_{\mathrm{D}}}(e_{\mathrm{D}}, \zeta_{\varepsilon}) = (\zeta_{\varepsilon} + \varepsilon)\varphi'_{e}(x, e_{\mathrm{D}} + e(u_{\varepsilon} - u_{\mathrm{D}})).$$
(2.50)

In particular, for  $e_{\rm D} = e(u_{\rm D})$ , we can still continue as

$$(\zeta_{\varepsilon} + \varepsilon)\varphi'_e(x, e_{\mathrm{D}} + e(u_{\varepsilon} - u_{\mathrm{D}})) = (\zeta_{\varepsilon} + \varepsilon)\varphi'_e(x, e(u_{\varepsilon})) =: \sigma_{\varepsilon}.$$
 (2.51)

#### Corollary 2.12 Setting

$$\mathfrak{s} \equiv \mathfrak{s}(\zeta) := \tau(e_{\mathrm{D}}, \zeta) \quad for \quad e_{\mathrm{D}} = e(u_{\mathrm{D}}) \quad with \quad u_{\mathrm{D}}|_{\Gamma} = w, \quad (2.52)$$

we obtain an effective stress and, moreover, it holds

$$\mathfrak{g}(\zeta) = \frac{1}{2} \int_{\Omega} \mathfrak{s}(\zeta) : e_{\mathrm{D}} \,\mathrm{d}x.$$
(2.53)

*Proof.* As  $f(\cdot, \zeta)$  is quadratic, in view of (2.45), we have the formula

$$\mathfrak{f}(e_{\mathrm{\scriptscriptstyle D}},\zeta) = \frac{1}{2} \int_{\Omega} \tau(e_{\mathrm{\scriptscriptstyle D}},\zeta) : e_{\mathrm{\scriptscriptstyle D}} \,\mathrm{d}x. \tag{2.54}$$

As a consequence of (2.36) with (2.10) and (2.37), we have  $g_{\varepsilon}(\zeta) = f_{\varepsilon}(u_{\rm D}, \zeta)$ , and this equality is inherited be the respective  $\Gamma$ -limits defined in (2.10) and (2.40), i.e. we have

$$\mathfrak{g}(\zeta) = \mathfrak{f}(e_{\mathrm{D}}, \zeta) \qquad \text{for } e_{\mathrm{D}} = e(u_{\mathrm{D}}) \text{ with } u_{\mathrm{D}}|_{\Gamma} = w.$$
 (2.55)

Substituting  $\mathfrak{s}$  defined by (2.52) into (2.54) and using (2.55), we obtain (2.53).

For the specific recovery sequence  $\{\zeta_{\varepsilon}\}$  from the proof of Proposition 2.10, by Lemma 2.11, the corresponding stresses  $\sigma_{\varepsilon}$  converge and we have  $\sigma_{\varepsilon} \rightharpoonup \mathfrak{s}(\zeta)$  so that, by the definition (2.31), we have  $\mathfrak{s}(\zeta) \in \mathfrak{S}(\zeta)$ . In view of (2.32), we can see that we have constructed a particular realizable stress  $\mathfrak{s}(\zeta)$  that attains the minimum in (2.32), i.e. an effective stress.  $\Box$ 

For further use it is important that (2.53) yields an explicit information about sensitivity of  $\mathfrak{g}(\zeta)$  with respect to  $u_{\rm D}$ .

### 3 Rate-independent damage evolution

Now, we will let the "hard-device" loading vary in time t ranging [0, T] with T > 0a fixed time horizon, i.e. w = w(t, x). Then the damage parameter will depend on both x and t, i.e.  $\zeta = \zeta(t, x)$ . Instead of  $G_{\varepsilon}(u, \zeta)$  from (2.9) with (2.8), we will consider

$$\mathcal{G}_{\varepsilon}(t, u, \zeta) := \begin{cases} V_{\varepsilon}(u, \zeta) & \text{if } u|_{\Gamma} = w(t, \cdot) \text{ and } \zeta \in Z, \\ +\infty & \text{elsewhere,} \end{cases}$$
(3.1)

where Z is again from (2.1). A further important concept consists in specific dissipation of energy during the damage process, which is given by a phenomenological activation threshold, denoted by a(x) > 0 (of a physical dimension  $J/m^d$ ) at a given spot  $x \in \Omega$ . Roughly speaking, the damage starts evolving when the elastic energy  $\varphi(e(u))$  reaches the activation threshold a, cf. (3.4b) and Sect. 3.1 for more details. At the same, a(x) says how much energy (per d-dimensional "volume") is dissipated by accomplishing the damage process, i.e. by decreasing  $\zeta(x)$  from 1 to 0.

The rate of energy dissipated in the whole body is then

$$R(\dot{\zeta}) := \int_{\Omega} \varrho(x, \dot{\zeta}(x)) \, \mathrm{d}x, \quad \text{where} \quad \varrho(x, \dot{z}) = \begin{cases} -a(x)\dot{z} & \text{if } \dot{z} \leq 0, \\ +\infty & \text{elsewhere.} \end{cases}$$
(3.2)

The value  $+\infty$  reflects that we consider damage as a *unidirectional process*, i.e. damage can only develop, but the material can never heal. We qualify the activation-threshold profile as:

$$a \in L^{\infty}(\Omega), \quad \operatorname{ess\,inf}_{x \in \Omega} a(x) > 0.$$
 (3.3)

## 3.1 Classical formulation of the regularized evolution problem

Let us first consider the regularized case with  $\varepsilon > 0$  where the displacement  $u_{\varepsilon} = u_{\varepsilon}(t,x)$  is well defined a.e. on the whole  $Q := (0,T) \times \Omega$ . The evolving damage profile will now also depend on  $\varepsilon$  hence we denote it by  $\zeta_{\varepsilon}$ . Taking into account our Gibbs energy (3.1) and the dissipation potential (3.2), the classical considerations in rational thermodynamics leads to the generalized force  $f \in -\partial_{(u,\zeta)}G_{\varepsilon}(t,u_{\varepsilon}(t),\zeta_{\varepsilon}(t))$  to belong to  $(0,\partial R(\frac{d\zeta_{\varepsilon}}{dt}))$ , where the notation  $\partial$  stands for subdifferential of the involved convex functionals. This, at least formally, leads to the classical formulation (cf. [12]) consisting in the balance of the stress and the evolution of the damage parameter:

div
$$(\sigma_{\varepsilon}) = 0$$
 with  $\sigma_{\varepsilon} = (\zeta_{\varepsilon} + \varepsilon)\varphi'_{e}(e(u_{\varepsilon})),$  (3.4a)  
$$\frac{\partial \zeta_{\varepsilon}}{\partial t} \leq 0,$$

$$\begin{array}{ccc}
\varphi(e(u_{\varepsilon})) - r_{\zeta_{\varepsilon}} - a - \operatorname{div}\left(\kappa |\nabla\zeta_{\varepsilon}|^{r-2}\nabla\zeta_{\varepsilon}\right) &\leq 0, \\
\frac{\partial\zeta_{\varepsilon}}{\partial t}\left(a - \varphi(e(u_{\varepsilon})) + \operatorname{div}\left(\kappa |\nabla\zeta_{\varepsilon}|^{r-2}\nabla\zeta_{\varepsilon}\right) + r_{\zeta_{\varepsilon}}\right) &= 0
\end{array}$$
(3.4b)

on Q, where  $r_{\zeta_{\varepsilon}} \in \partial \chi_{[0,1]}(\zeta_{\varepsilon})$ . The notation  $\chi_{[0,1]}$  stands for the indicator function of the interval [0,1] where the damage parameter ranges; in fact,  $[0,+\infty)$  can be used equally. The complementarity problem (3.4b) represents the evolution inclusion

$$\partial_{\dot{\zeta}} \varrho \left( x, \frac{\partial \zeta_{\varepsilon}}{\partial t} \right) - \kappa \operatorname{div} \left( |\nabla \zeta_{\varepsilon}|^{r-2} \nabla \zeta_{\varepsilon} \right) + \varphi(x, e(u_{\varepsilon})) + \partial \chi_{[0,1]}(\zeta_{\varepsilon}) \ni 0.$$
(3.5)

The second inequality in (3.4b) can bear the interpretation that the driving force for the damage process can be identified as the specific energy  $\varphi(x, e(u_{\varepsilon}))$  and the damage evolves if it reaches the *activation threshold* a(x) modified by the term  $\operatorname{div}(\kappa(x)|\nabla\zeta_{\varepsilon}(x)|^{r-2}\nabla\zeta_{\varepsilon}(x))$  which reflect in some way *hardening-like* effects (if the spot x is surrounded by a less damaged material) or softening (in an opposite case); we refer to [1].

We must complete the system by some boundary conditions not only for  $u_{\varepsilon}$  but now also for the damage  $\zeta_{\varepsilon}$ . In accord with previous sections, we assume the mentioned Dirichlet conditions for  $u_{\varepsilon}$  combined with zero normal stress implicitly imposed already in (2.3) while for  $\zeta_{\varepsilon}$  we assumed, for simplicity, zero Neumann condition as any condition for it is a bit artificial anyhow. Hence,

$$u_{\varepsilon} = w$$
 on  $\Gamma$ , (3.6a)

$$\sigma_{\varepsilon}\nu = 0 \qquad \text{on } \partial\Omega \setminus \Gamma, \tag{3.6b}$$

$$\frac{\partial \zeta_{\varepsilon}}{\partial \nu} = 0 \qquad \text{on } \partial \Omega. \tag{3.6c}$$

An initial condition should be prescribed for the damage parameter, considering some prescribed initial profile  $\zeta_0$  and, rather formally, also the initial displacement  $u_0$  (qualified later):

$$\zeta_{\varepsilon}(0,\cdot) = \zeta_0, \quad u_{\varepsilon}(0,\cdot) = u_0 \quad \text{on} \quad \Omega.$$
(3.7)

#### 3.2 Energetic solution of the regularized problem

The relevant and mathematically amenable concept of a "weak solution" to the doubly-nonlinear problem (3.5) with degree-1 homogeneous  $\rho(x, \cdot)$  is a so-called *energetic solution*, formulated in [30, 31], see also [26] for a survey. Recently, this concept was also exposed in the context of  $\Gamma$ -limits in [29].

Let us first derive it formally from (3.4). For this, let us consider  $u_{\rm D}(t, \cdot)$  as a suitable (qualified later) extension of  $w(t, \cdot)$ . The weak formulation of the Euler-Lagrange equation (3.4a) tested by  $\frac{\partial}{\partial t}(u_{\varepsilon} - u_{\rm D})$ , which has zero traces and is thus a legal test function, yields  $\int_{\Omega} \sigma_{\varepsilon} : e(\frac{\partial}{\partial t}u_{\varepsilon}) dx = \int_{\Omega} \sigma_{\varepsilon} : e(\frac{\partial}{\partial t}u_{\rm D}) dx$ . Then, as there is no explicit dependence of  $\mathcal{G}_{\varepsilon}$  on t in (3.1),  $\frac{\partial}{\partial t}\mathcal{G}_{\varepsilon} = 0$  and we can formally apply the chain rule in the form

$$\frac{\mathrm{d}}{\mathrm{d}t}\mathcal{G}_{\varepsilon}(t, u_{\varepsilon}(t), \zeta_{\varepsilon}(t)) = \int_{\Omega} \sigma_{\varepsilon} \cdot e\left(\frac{\partial u_{\varepsilon}}{\partial t}\right) + \varphi(e(u_{\varepsilon})) \frac{\partial \zeta_{\varepsilon}}{\partial t} + \kappa |\nabla \zeta_{\varepsilon}|^{r-2} \nabla \zeta_{\varepsilon} \cdot \nabla \frac{\partial \zeta_{\varepsilon}}{\partial t} \,\mathrm{d}x$$

$$= \int_{\Omega} \sigma_{\varepsilon} \cdot e\left(\frac{\partial u_{\mathrm{D}}}{\partial t}\right) + \varphi(e(u_{\varepsilon})) \frac{\partial \zeta_{\varepsilon}}{\partial t} + \kappa |\nabla \zeta_{\varepsilon}|^{r-2} \nabla \zeta_{\varepsilon} \cdot \nabla \frac{\partial \zeta_{\varepsilon}}{\partial t} \,\mathrm{d}x. \tag{3.8}$$

Using (3.5) in the weak formulation tested formally by  $\frac{\partial}{\partial t}\zeta_{\varepsilon}$  together with (3.6c), one gets

$$\int_{\Omega} \varphi(x, e(u_{\varepsilon})) \frac{\partial \zeta_{\varepsilon}}{\partial t} + \kappa |\nabla \zeta_{\varepsilon}|^{r-2} \nabla \zeta_{\varepsilon} \cdot \nabla \frac{\partial \zeta_{\varepsilon}}{\partial t} \, \mathrm{d}x = -\int_{\Omega} \partial_{\zeta} \varrho\left(x, \frac{\partial \zeta_{\varepsilon}}{\partial t}\right) \frac{\partial \zeta_{\varepsilon}}{\partial t} \, \mathrm{d}x \\ = -\int_{\Omega} \varrho\left(x, \frac{\partial \zeta_{\varepsilon}}{\partial t}\right) \, \mathrm{d}x = -R\left(\frac{\partial \zeta_{\varepsilon}}{\partial t}\right) \, (3.9)$$

due to the degree-1 homogeneity of  $\varrho(x, \cdot)$ , see definition (3.2). Putting (3.9) into (3.8), integrating it over a time interval  $[t_1, t_2]$ , and expressing the dissipated energy  $\int_{t_1}^{t_2} R(\frac{\partial}{\partial t}\zeta(t)) dt$  as the total variation without referring explicitly to the time derivative  $\frac{\partial}{\partial t}\zeta$ , i.e.

$$\operatorname{Var}_{R}(\zeta; t_{1}, t_{2}) := \sup \sum_{i=1}^{j} R(\zeta(s_{i}) - \zeta(s_{i-1}))$$
(3.10)

with the supremum taken over all  $j \in \mathbb{N}$  and over all partitions of  $[t_1, t_2]$  in the form  $t_1 = s_0 < s_1 < \ldots < s_{j-1} < s_j = t_2$ , we eventually obtain

$$\mathcal{G}_{\varepsilon}(t_{2}, u_{\varepsilon}(t_{2}), \zeta_{\varepsilon}(t_{2})) + \operatorname{Var}_{R}(\zeta_{\varepsilon}; t_{1}, t_{2}) = \mathcal{G}_{\varepsilon}(t_{1}, u_{\varepsilon}(t_{1}), \zeta_{\varepsilon}(t_{1})) + \int_{t_{1}}^{t_{2}} \int_{\Omega} \sigma_{\varepsilon} : e\left(\frac{\partial u_{\mathrm{D}}}{\partial t}\right) \mathrm{d}x \, \mathrm{d}t \qquad (3.11)$$

In our special situation with R defined via (3.2), we have simply

$$\operatorname{Var}_{R}(\zeta; t_{1}, t_{2}) = R(\zeta(t_{1}) - \zeta(t_{2}))$$

$$= \begin{cases} \int_{\Omega} a(x) (\zeta(t_{1}, x) - \zeta(t_{2}, x)) \, \mathrm{d}x & \text{if } \zeta(\cdot, x) \text{ is nondecreasing} \\ & \text{on } [t_{1}, t_{2}] \text{ for a.a. } x \in \Omega, \\ +\infty & \text{otherwise.} \end{cases}$$

$$(3.12)$$

The particular terms in (3.11) represent respectively:

- the stored energy at the final time  $t_2$ ,
- the energy dissipated by damage during the time interval  $[t_1, t_2]$ ,
- the stored energy at the initial time  $t_1$ , and
- the work done by external loadings during the time interval  $[t_1, t_2]$ .

The global-minimization hypothesis related to (3.4a) is related with a *stability* property, i.e.

$$\forall (\tilde{u}, \tilde{\zeta}) \in W^{1,2}(\Omega; \mathbb{R}^d) \times Z, \quad \tilde{u}|_{\Gamma} = w(t) :$$
  
$$\mathcal{G}_{\varepsilon}(t, u_{\varepsilon}(t), \zeta_{\varepsilon}(t)) \leq \mathcal{G}_{\varepsilon}(t, \tilde{u}, \tilde{\zeta}) + R(\tilde{\zeta} - \zeta_{\varepsilon}(t)). \quad (3.13)$$

The philosophy of (3.13) is that the gain of Gibbs' energy  $\mathcal{G}_{\varepsilon}(t, u_{\varepsilon}(t), \zeta_{\varepsilon}(t)) - \mathcal{G}_{\varepsilon}(t, \tilde{u}, \tilde{\zeta})$  at any other state  $(\tilde{u}, \tilde{\zeta})$  is not larger than the dissipation  $R(\tilde{\zeta} - \zeta_{\varepsilon}(t))$ ; cf. [31] for discussion.

Now, following [30], see also [26, 31], we introduce a definition of an energetic solution to the considered problem. By B([0,T];X) or BV([0,T];X) we denote the Banach space of bounded Bochner-measurable or bounded-variation X-valued mappings defined everywhere on [0,T], respectively.

**Definition 3.1** (*Energetic solution to the regularized problem.*) A process  $(u_{\varepsilon}, \zeta_{\varepsilon}) : [0,T] \to W^{1,2}(\Omega; \mathbb{R}^d) \times Z$  is called an *energetic solution* to the problem (3.4) and (3.6)–(3.7), i.e. given by the data  $\varphi, \kappa, \varrho, r, w, u_0, \zeta_0$ , and  $\varepsilon > 0$ , if, beside (3.7), also

- (i)  $(u_{\varepsilon}, \zeta_{\varepsilon}) \in B([0, T]; W^{1,2}(\Omega; \mathbb{R}^d)) \times (BV([0, T]; L^1(\Omega)) \cap B([0, T]; W^{1,r}(\Omega))),$
- (ii) it is stable in the sense that (3.13) holds for all  $t \in [0, T]$ , and
- (iii) the energy balance (3.11) holds for any  $0 \le t_1 < t_2 \le T$  and, in particular, the function  $t \mapsto \int_{\Omega} \sigma_{\varepsilon} : e(\frac{\partial}{\partial t}u_{\mathrm{D}}) \,\mathrm{d}x$  belongs to  $L^1(0,T)$ .

**Remark 3.2** In fact, Definition 3.1 is based on a *global-minimization* hypothesis competing with the *maximum-dissipation* principle (or rather *Levitas' realizability principle* [21]).

**Remark 3.3** (Normal stress: reaction to the Dirichlet loading.) Due to (2.20) and Definition 3.1(i),  $\sigma_{\varepsilon} \in B([0,T]; L^2(\Omega; \mathbb{R}^{d \times d}_{sym}))$  and, in order to ensure that  $t \mapsto \int_{\Omega} \sigma_{\varepsilon}$ :  $e(\frac{\partial}{\partial t}u_{\mathrm{D}}) \,\mathrm{d}x$  belongs to  $L^1(0,T)$ , one needs just  $u_{\mathrm{D}} \in W^{1,1}([0,T]; W^{1,2}(\Omega; \mathbb{R}^d))$ . In fact, one needs only to qualify  $w \in W^{1,1}([0,T]; W^{1/2,2}(\Gamma; \mathbb{R}^d))$  because then such extension  $u_{\mathrm{D}}$  of it will always exists. Even more, (3.11) and thus the whole Definition 3.1 depends only on w and not on any particular choice of its extension  $u_{\mathrm{D}}$ . Actually, we could define the normal stress  $\vec{\sigma}_{\varepsilon}$  as the linear bounded functional on  $W^{1/2,2}(\Gamma; \mathbb{R}^d)$  by the formula

$$\langle \vec{\sigma}_{\varepsilon}, v |_{\Gamma} \rangle = \int_{\Omega} \sigma_{\varepsilon} : e(v(x)) \, \mathrm{d}x.$$
 (3.14)

It is a consequence of the stability (3.13) with  $\tilde{\zeta} := \zeta_{\varepsilon}(t)$  that  $u_{\varepsilon}(t)$  minimizes  $G_{\varepsilon}(t, \cdot, \zeta_{\varepsilon}(t))$  so that the corresponding Euler-Lagrange equation, cf. (2.28) for the static case, says in particular that

$$\operatorname{div}(\sigma_{\varepsilon}) = 0$$
 in the sense of distributions on  $Q$ . (3.15)

Then the right-hand side of (3.14) is independent of the particular extension v of  $v|_{\Gamma}$  into  $\Omega$  and thus the normal stress  $\vec{\sigma}_{\varepsilon}$  is well defined by (3.14). This can easily be seen by an extension of Green's formula using Neumann boundary conditions (3.6b) and by the symmetry of the stress tensor

$$0 = \int_{\Omega} \operatorname{div}(\sigma_{\varepsilon}) \cdot v \, \mathrm{d}x = \int_{\partial\Omega} (\sigma_{\varepsilon}\nu) \cdot v \, \mathrm{d}S - \int_{\Omega} \sigma_{\varepsilon} : \nabla v \, \mathrm{d}x = \int_{\Gamma} (\sigma_{\varepsilon}\nu) \cdot v \, \mathrm{d}S - \int_{\Omega} \sigma_{\varepsilon} : e(v) \, \mathrm{d}x,$$

In a regular case thus  $\vec{\sigma}_{\varepsilon} = \sigma_{\varepsilon}\nu$ . The last term in (3.11) can equivalently be expressed as  $\int_{t_1}^{t_2} \langle \vec{\sigma}_{\varepsilon}, \frac{\partial w}{\partial t} \rangle dt$ , which is just the more explicit form of the work of the external "hard-device" load  $\int_{t_1}^{t_2} \int_{\Gamma} \vec{\sigma}_{\varepsilon} \cdot \frac{\partial w}{\partial t} \, dS \, dt$ . In what follows, we will confine ourselves to

$$w \in C^1(I; W^{1/2,2}(\Gamma; \mathbb{R}^d)),$$
 (3.16)

which has nearly the same generality in the context of rate-independent processes and makes the proofs easier, cf. in particular [29, Assumption (2.8)] pointed also out later in Remark 3.9. Then (3.16) allows for considering  $u_{\rm D} \in C^1([0,T]; W^{1,2}(\Omega; \mathbb{R}^d))$ .

**Proposition 3.4** (Existence of energetic solutions to  $\varepsilon$ -problems.) (See [27].) Let (2.6), (3.3), (3.16),  $(u_0, \zeta_0) \in W^{1,2}(\Omega; \mathbb{R}^d) \times Z$  be stable in the sense

$$\forall (\tilde{u}, \tilde{\zeta}) \in W^{1,2}(\Omega; \mathbb{R}^d) \times Z, \quad \tilde{u}|_{\Gamma} = w(0, \cdot) :$$
  
$$\mathcal{G}_{\varepsilon}(0, u_0, \zeta_0) \leq \mathcal{G}_{\varepsilon}(0, \tilde{u}, \tilde{\zeta}) + R(\zeta_0 - \tilde{\zeta}), \qquad (3.17)$$

and let  $\varepsilon > 0$ . Then a solution  $(u_{\varepsilon}, \zeta_{\varepsilon})$  in the sense of Definition 3.1 does exist.

Comments to the proof. The above assertion has been proved, except the Bochner measurability of  $u_{\varepsilon}$ , in [27] for the case  $\varphi$  and  $\varrho$  independent of x but our x-dependent generalization is trivial. Also, a special loading and initial stable initial condition was chosen in [27], namely  $w(0, \cdot) = 0$ ,  $u_0 = 0$ ,  $\zeta_0 = 1$ , i.e. unloaded undamaged body at the original time. Our, only slightly more general initial condition makes just a trivial and standard modification, cf. [12, 26, 28, 29]. Also,  $w \in W^{1,1}(I; W^{1,\infty}(\Gamma; \mathbb{R}^d))$ has been used in [27] but the generalization to  $w \in W^{1,1}(I; W^{1/2,2}(\Gamma; \mathbb{R}^d))$  is routine since, unlike [27], we do not treat any contact problem at large strains and then (3.16) works, too.

Due to our formula  $u_{\varepsilon}(t) = u_{\mathrm{D}}(t) + L_{\zeta_{\varepsilon}(t)+\varepsilon}e(u_{\mathrm{D}}(t))$ , the claimed Bochner measurability of  $u_{\varepsilon}$  in time, not proved in [27], is here a simple consequence of the measurability of  $\zeta_{\varepsilon} : [0,T] \to W^{1,r}(\Omega)$  and of the continuity of the mapping  $(e_{\mathrm{D}},\zeta) \mapsto v := L_{\zeta+\varepsilon}e_{\mathrm{D}}$ as a mapping  $L^2(\Omega; \mathbb{R}^{d\times d}_{\mathrm{sym}}) \times W^{1,r}(\Omega) \to W_{\Gamma}^{1,2}(\Omega; \mathbb{R}^d)$ . The mentioned measurability of  $\zeta_{\varepsilon}$  follows from measurability of the BV-function  $\zeta_{\varepsilon} : [0,T] \to L^1(\Omega)$  and from the a-priori estimate of  $\{\zeta_{\varepsilon}(t)\}_{t\in[0,T]}$  in the separable space  $W^{1,r}(\Omega)$  by Pettis' theorem. The mentioned (even locally Lipschitz  $(L^2 \times L^{\infty}, W^{1,2})$ -) continuity of  $(e_{\mathrm{D}}, \zeta) \mapsto v := L_{\zeta+\varepsilon}e_{\mathrm{D}}$  can be proved quite standardly: We take the Euler-Lagrange equation for  $v := L_{\zeta+\varepsilon}e_{\mathrm{D}}$  defined in (2.38), i.e. in the weak formulation  $\int_{\Omega} \zeta \mathbb{C}(e_{\mathrm{D}} + e(v)) : e(z) \, dx = 0$  for all  $z \in W_{\Gamma}^{1,2}(\Omega; \mathbb{R}^d)$ . Considering other  $\tilde{e}_{\mathrm{D}}, \tilde{\zeta}$ , and  $\tilde{v} := L_{\tilde{\zeta}+\varepsilon}\tilde{e}_{\mathrm{D}}$ , we have  $\int_{\Omega} \tilde{\zeta} \mathbb{C}(\tilde{e}_{\mathrm{D}} + e(\tilde{v})) : e(z) \, dx = 0$ . Subtracting these equations and testing the difference by  $z := v - \tilde{v}$  gives, after some algebra and Hölder's and Young's inequalities,

$$\begin{split} \varepsilon\eta \big\| e(v-\tilde{v}) \big\|_{L^2(\Omega;\mathbb{R}^{d\times d}_{\mathrm{sym}})}^2 &\leq \int_{\Omega} (\zeta+\varepsilon) \mathbb{C}(e(v-\tilde{v})) : e(v-\tilde{v}) \,\mathrm{d}x \\ &= \int_{\Omega} (\zeta-\tilde{\zeta}) \mathbb{C}(e_{\mathrm{D}}+e(\tilde{v})) : e(v-\tilde{v}) + (\tilde{\zeta}+\varepsilon) \mathbb{C}(e_{\mathrm{D}}-\tilde{e}_{\mathrm{D}}) : e(v-\tilde{v}) \,\mathrm{d}x \\ &\leq C \|\zeta-\tilde{\zeta}\|_{L^{\infty}(\Omega)}^2 + C \|e_{\mathrm{D}}-\tilde{e}_{\mathrm{D}}\|_{L^2(\Omega;\mathbb{R}^{d\times d}_{\mathrm{sym}})}^2 + \frac{\varepsilon\eta}{2} \big\| e(v-\tilde{v}) \big\|_{L^2(\Omega;\mathbb{R}^{d\times d}_{\mathrm{sym}})}^2 \end{split}$$

with  $\eta > 0$  from (2.6b) and with  $C = \max(\|e_{\mathrm{D}} + e(\tilde{v})\|_{L^{2}(\Omega;\mathbb{R}^{d\times d}_{\mathrm{sym}})}, \|\zeta\|_{L^{\infty}(\Omega)} + \varepsilon)^{2}/(\varepsilon\eta)$ . Absorbing the last term in the left-hand side and involving still Korn's inequality  $\|v - \tilde{v}\|_{W^{1,2}(\Omega;\mathbb{R}^{d})} \leq K_{\Omega,\Gamma} \|e(v - \tilde{v})\|_{L^{2}(\Omega;\mathbb{R}^{d\times d}_{\mathrm{sym}})}$ , we clearly get the claim continuity.  $\Box$ 

#### 3.3 Energetic solution of the complete-damage problem

Let us observe that, due to the definition (3.1) with (2.29),

$$\mathcal{G}_{\varepsilon}(t, u_{\varepsilon}(t), \zeta_{\varepsilon}(t)) = \int_{\Omega} \frac{1}{2} \sigma_{\varepsilon}(t, x) : e(u_{\mathrm{D}}(t, x)) + \frac{\kappa(x)}{r} |\nabla \zeta_{\varepsilon}(t, x)|^{r} \mathrm{d}x, \qquad (3.18)$$

hence both (3.11) and (3.13) can be expressed in terms of  $\sigma_{\varepsilon}$  and  $\zeta_{\varepsilon}$ . Moreover, as explained above, (3.15) implies that  $\sigma_{\varepsilon}$  itself is essentially determined by  $\zeta_{\varepsilon}(t, \cdot)$  and  $w(t, \cdot)$ .

Like (2.10), let us now define

$$\boldsymbol{g}(t,\zeta) := \liminf_{\substack{\varepsilon \to 0+, \quad \tilde{\zeta} \in Z, \\ \tilde{\zeta} \to \zeta \text{ in } W^{1,r}(\Omega)}} \min_{u \in W^{1,2}(\Omega; \mathbb{R}^d)} \mathcal{G}_{\varepsilon}(t,u,\tilde{\zeta})$$
(3.19)

with  $\mathcal{G}_{\varepsilon}$  defined in (3.1). Since  $\min_{u \in W^{1,2}(\Omega;\mathbb{R}^d)} \mathcal{G}_{\varepsilon}(t, u, \tilde{\zeta}) = f_{\varepsilon}(e(u_{\mathrm{D}}(t)), \tilde{\zeta}) + \int_{\Omega} \frac{\kappa}{r} |\nabla \tilde{\zeta}|^r \, \mathrm{d}x$  with  $f_{\varepsilon}$  from (2.37), we have equivalently

$$\boldsymbol{g}(t,\zeta) = \liminf_{\substack{\varepsilon \to 0+, \quad \tilde{\zeta} \in Z, \\ \tilde{\zeta} \to \zeta \text{ in } W^{1,r}(\Omega)}} f_{\varepsilon}(e(u_{\mathrm{D}}(t)), \tilde{\zeta}) + \int_{\Omega} \frac{\kappa}{r} |\nabla \tilde{\zeta}|^{r} \, \mathrm{d}x.$$
(3.20)

**Lemma 3.5** Any recovery sequence  $\{\zeta_{\varepsilon}\}_{\varepsilon>0} \subset Z$  for (3.20), i.e.  $\zeta_{\varepsilon} \rightharpoonup \zeta$  and  $f_{\varepsilon}(e(u_{\mathrm{D}}(t)), \zeta_{\varepsilon}) + \int_{\Omega} \frac{\kappa}{r} |\nabla \zeta_{\varepsilon}|^r \, \mathrm{d}x \rightarrow \boldsymbol{g}(t, \zeta)$ , in fact converges strongly. Moreover, referring to  $\mathfrak{f}(u_{\mathrm{D}}, \zeta)$  defined by (2.40), we have now

$$\boldsymbol{g}(t,\zeta) = \mathfrak{f}(\boldsymbol{e}(\boldsymbol{u}_{\mathrm{D}}(t),\zeta) + \int_{\Omega} \frac{\kappa}{r} \left| \nabla \zeta \right|^{r} \,\mathrm{d}x. \tag{3.21}$$

*Proof.* First, we prove (3.21). The inequality " $\geq$ " is by the weak lower semicontinuity of  $\zeta \mapsto \int_{\Omega} \kappa |\nabla \zeta|^r \, dx$  and by the definition of the  $\Gamma$ -limits  $\boldsymbol{g}$  and  $\mathfrak{f}$  in (3.19) and (2.40), respectively. It suffices to take any recovery sequence  $\{\zeta_{\varepsilon}\}_{\varepsilon>0}$  for  $\boldsymbol{g}$  and make a limit passage in

$$\boldsymbol{g}(t,\zeta) = \lim_{\varepsilon \to 0+} \min_{u \in W^{1,2}(\Omega)} \mathcal{G}_{\varepsilon}(t,u,\zeta_{\varepsilon}) = \lim_{\varepsilon \to 0+} \left( f_{\varepsilon}(e(u_{\mathrm{D}}(t)),\zeta_{\varepsilon}) + \int_{\Omega} \frac{\kappa}{r} |\nabla\zeta_{\varepsilon}|^{r} \mathrm{d}x \right)$$
  

$$\geq \liminf_{\varepsilon \to 0+} f_{\varepsilon}(e(u_{\mathrm{D}}(t)),\zeta_{\varepsilon}) + \liminf_{\varepsilon \to 0+} \int_{\Omega} \frac{\kappa}{r} |\nabla\zeta_{\varepsilon}|^{r} \mathrm{d}x$$
  

$$\geq \mathfrak{f}(e(u_{\mathrm{D}}(t)),\zeta) + \int_{\Omega} \frac{\kappa}{r} |\nabla\zeta|^{r} \mathrm{d}x.$$
(3.22)

The opposite inequality " $\leq$ " is by the same limit passage but now using the special recovery sequence  $\zeta_{\varepsilon} = (\zeta - \delta_{\varepsilon})^+$  for  $\mathfrak{f}$  from the proof of Proposition 2.10. It converges to  $\zeta$  not only weakly but also strongly. Indeed,  $\nabla \zeta_{\varepsilon}(x) \to \nabla \zeta(x)$  for a.a.  $x \in \Omega$  because  $\nabla \zeta = 0 = \nabla \zeta_{\varepsilon}$  a.e. on  $N_{\zeta}$  and because, for a.a.  $x \in \Omega \setminus N_{\zeta}$ , there is  $\varepsilon_x > 0$  such that  $0 < \zeta_{\varepsilon}(x) = \zeta(x) - \delta_{\varepsilon}$  and thus  $\nabla \zeta_{\varepsilon}(x) = \nabla \zeta(x)$  for all  $0 < \varepsilon < \varepsilon_x$ , and then, by Lebesgue dominated-convergence theorem,  $\int_{\Omega} |\nabla \zeta_{\varepsilon}(x)|^r dx \to \int_{\Omega} |\nabla \zeta(x)|^r dx$  and, having convergence of the norms as well as weak convergence, we can conclude strong convergence by uniform convexity of  $W^{1,r}(\Omega)$  and a Fan-Glicksberg type theorem.

Let us now consider an arbitrary recovery sequence  $\{\zeta_{\varepsilon}\}_{\varepsilon>0} \subset Z$  for (3.19). Denote  $\widehat{\alpha} = \int_{\Omega} \frac{\kappa}{r} |\nabla \zeta|^r \, dx$ . For a subsequence and some  $\alpha$  and  $\beta$ ,  $\int_{\Omega} \frac{\kappa}{r} |\nabla \zeta_{\varepsilon}|^r \, dx \to \alpha$  and  $f_{\varepsilon}(e(u_{\mathrm{D}}(t)), \zeta_{\varepsilon}) \to \beta$ . Simultaneously,  $f_{\varepsilon}(e(u_{\mathrm{D}}(t)), \zeta_{\varepsilon}) + \int_{\Omega} \frac{\kappa}{r} |\nabla \zeta_{\varepsilon}|^r \, dx \to g(t, \zeta) = \alpha + \beta$ . By the weak lower semicontinuity, always  $\widehat{\alpha} \leq \alpha$ . Assume  $\widehat{\alpha} < \alpha$ . Using (3.21), we would have

$$\beta = \lim_{\varepsilon \to 0+} f_{\varepsilon}(e(u_{\mathrm{D}}(t)), \zeta_{\varepsilon}) = \lim_{\varepsilon \to 0+} \left( \boldsymbol{g}(t, \zeta) - \int_{\Omega} \frac{\kappa}{r} |\nabla \zeta_{\varepsilon}|^{r} \mathrm{d}x \right)$$
$$= \boldsymbol{g}(t, \zeta) - \alpha < \boldsymbol{g}(t, \zeta) - \widehat{\alpha} = \mathfrak{f}(e(u_{\mathrm{D}}(t)), \zeta), \qquad (3.23)$$

a contradiction with (2.40). Hence  $\widehat{\alpha} = \alpha$  and we have  $\int_{\Omega} \frac{\kappa}{r} |\nabla \zeta_{\varepsilon}|^r \, dx \to \alpha = \widehat{\alpha} = \int_{\Omega} \frac{\kappa}{r} |\nabla \zeta|^r \, dx$ . Due to the strict convexity of the integrand  $\kappa(x)| \cdot |^r$  and due to the weak convergence  $\zeta_{\varepsilon} \to \zeta$ , we can conclude strong convergence, cf. e.g. [35].  $\Box$ 

Considering an effective stress, as in (2.53), we can write

$$\boldsymbol{g}(t,\zeta) = \int_{\Omega} \frac{1}{2} \boldsymbol{\mathfrak{s}}(t,\zeta) : e(\boldsymbol{u}_{\mathrm{D}}(t)) + \frac{\kappa}{r} |\nabla\zeta|^r \, \mathrm{d}x.$$
(3.24)

Motivated by this and by the investigations for  $\varepsilon \to 0$  in the static case in Sect. 2, we introduce the following "energetic" definition without referring to the problem (3.4) for  $\varepsilon = 0$  because the displacement need not have a well defined sense any longer. For simplicity and without much restriction for possible applications, we consider the initial damage profile from Z away from zero

$$\min_{x \in \Omega} \zeta_0(x) > 0. \tag{3.25}$$

Then, prescribing the initial displacement  $u_0$  makes sense and we thus automatically prescribe also the initial stress  $\sigma(0) = \zeta_0 \varphi'_e(e(u_0))$ . As for the stability (3.17) of the initial conditions, for example, w(0) = 0,  $u_0 = 0$  and  $0 < \zeta_0 \leq 1$  constant will satisfy (3.17) even for any  $\varepsilon > 0$ , which is what we will assume later in Theorem 3.7. This can be however satisfied for some non-constant damage profiles  $\zeta_0$  too, depending on  $a(\cdot)$  and  $\kappa(\cdot)$ .

Definition 3.6 (*Energetic solution to the complete-damage problem.*) The process  $(\mathfrak{s}, \zeta)$  :  $[0,T] \rightarrow L^2(\Omega; \mathbb{R}^{d \times d}_{sym}) \times Z$  is called an *energetic solution* to the problem given by the data  $\varphi$ ,  $\varrho$ , w, and  $\zeta_0$ , if, beside (3.7), also

- (i)  $(\mathfrak{s},\zeta) \in \mathcal{B}([0,T]; L^2(\Omega; \mathbb{R}^{d \times d})) \times (\mathcal{BV}([0,T]; L^1(\Omega)) \cap \mathcal{B}([0,T]; W^{1,r}(\Omega)),$
- (ii) it is stable in the sense that

$$\boldsymbol{g}(t,\zeta(t)) \leq \boldsymbol{g}(t,\tilde{\zeta}) + \int_{\Omega} \varrho(x,\tilde{\zeta}-\zeta(t)) \,\mathrm{d}x \quad \text{for any } \tilde{\zeta} \in \mathbb{Z}, \text{ and } (3.26)$$

(iii) and, for any  $0 \le t_1 < t_2 \le T$ , the energy equality holds:

$$\boldsymbol{g}(t_2,\zeta(t_2)) + \operatorname{Var}_R(\zeta;t_1,t_2) = \boldsymbol{g}(t_1,\zeta(t_1)) + \int_{t_1}^{t_2} \int_{\Omega} \boldsymbol{\mathfrak{s}} : e\left(\frac{\partial u_{\mathrm{D}}}{\partial t}\right) \, \mathrm{d}x \, \mathrm{d}t(3.27)$$

in particular, the function  $t \mapsto \int_{\Omega} \mathfrak{s}(t,x) : e(\frac{\partial u_{\mathrm{D}}}{\partial t}(t,x)) \, \mathrm{d}x$  belongs to  $L^1(0,T)$ ,

(iv) div( $\mathfrak{s}$ ) = 0 in the sense of distributions and  $\mathfrak{s}(t)$  is an effective stress with respect to  $\zeta(t)$  and w(t) for any  $t \in [0, T]$ ; in particular (3.24) holds.

**Theorem 3.7** (Existence of energetic solutions, convergence of  $(u_{\varepsilon}, \zeta_{\varepsilon})$ .) Let (2.6), (3.3),  $w \in C^1([0,T]; W^{1/2,2}(\Gamma; \mathbb{R}^d))$ ,  $(u_0, \zeta_0) \in W^{1,2}(\Omega; \mathbb{R}^d) \times Z$  satisfy (3.17) for all  $\varepsilon > 0$  and (3.25). Then, there exists a subsequence  $\{\varepsilon_n\}_{n \in \mathbb{N}}$  converging to 0 and a process  $(\mathfrak{s}, \zeta) : [0,T] \to L^2(\Omega; \mathbb{R}^{d \times d}) \times Z$  being an energetic solution according to Definition 3.6, in particular  $u_{\mathsf{D}} \in C^1([0,T]; W^{1,2}(\Omega; \mathbb{R}^d))$  is considered for (3.27) in accord with Remark 3.3, such that the following holds for all  $t \in [0,T]$ : (i)  $\mathcal{E}_{\varepsilon_n}(t, u_{\varepsilon_n}(t), \zeta_{\varepsilon_n}(t)) \to \mathbf{g}(t, \zeta(t))$ ,

- (ii)  $\operatorname{Var}_R(\zeta_{\varepsilon_n}; 0, t) \to \operatorname{Var}_R(\zeta; 0, t),$
- (iii)  $\zeta_{\varepsilon_n}(t) \to \zeta(t)$  strongly in  $W^{1,r}(\Omega)$ ,
- (iv)  $\sigma_{\varepsilon_n}(t) = (\zeta_{\varepsilon_n}(t) + \varepsilon)\varphi'_e(e(u_{\varepsilon_n}(t))) \rightharpoonup \mathfrak{s}(t)$  weakly in  $L^2(\Omega; \mathbb{R}^{d \times d}_{svm})$ .

Proof. Most of the assertions have been proved in [27, Sect.4] but the most essential properties remained open in the context of non-quadratic quasiconvex  $\varphi$  considered there. Namely, only an energy inequality in (3.27) has been proved in [27], only the weak convergence of  $\zeta_{\varepsilon_n}(t) \rightharpoonup \zeta(t)$  instead of (iii), and, instead of the properties claimed in Definition 3.6(iv),  $\mathfrak{s}(t)$  was shown only a realizable stress only. Moreover, instead of (iv), only  $\sigma_{\varepsilon_n} \rightharpoonup \mathfrak{s}$  weakly\* in  $L^{\infty}(0,T; L^2(\Omega; \mathbb{R}^{d\times d}_{sym}))$  was proved in [27]. Let us remark that, in fact, instead of  $(\zeta + \varepsilon)\varphi(e)$ , the regularization  $\zeta\varphi(e) + \varepsilon |e|^2$ has been used in [27], homogeneous material (i.e.  $\varphi, \varrho, a$ , and  $\kappa$  independent of x), and only special initial conditions  $u_0 = 0$ ,  $\zeta_0 = 1$ , w(0) = 0 were considered, but these modifications are easy under our data qualification. Let us now prove the remaining properties.

The property  $\operatorname{div}(\mathfrak{s}) = 0$  claimed in Definition 3.6(iv) is inherited by a trivial limit passage from (3.15).

Due to (i),  $\{\zeta_{\varepsilon_n}\}_{n\in\mathbb{N}}$  is a recovery sequence for (3.20), by Lemma 3.5 we have strong convergence in (iii). Moreover, by Lemma 2.11, we have  $\sigma_{\varepsilon_n}(t) \rightharpoonup \tau(e(u_{\mathrm{D}}(t)), \zeta(t))$ . Hence, modifying  $\mathfrak{s}$  obtained in [27], if necessary, on a zero-measure set on [0, T], we have  $\mathfrak{s}(t) = \tau(e(u_{\mathrm{D}}(t)), \zeta(t))$  and  $\mathfrak{s}(t)$  being thus proved an essential stress. Energy equality in (3.27) is then a consequence of [26, Proposition 5.7] provided one shows the power of external loading to be in  $L^{\infty}(0,T)$  and the last term in (3.27) to be equal to  $\int_{t_1}^{t_2} \frac{\partial g}{\partial t}(t,\zeta(t)) dt$ . Here, by using successively (3.21), (2.54), and (2.45), for any  $\zeta \in Z$  fixed, we have

$$\boldsymbol{g}(t,\zeta) = \boldsymbol{\mathfrak{f}}(\boldsymbol{e}(\boldsymbol{u}_{\mathrm{D}}(t),\zeta) + \int_{\Omega} \frac{\kappa}{r} |\nabla\zeta|^{r} \,\mathrm{d}x \\
= \int_{\Omega} \frac{1}{2} \tau(\boldsymbol{e}(\boldsymbol{u}_{\mathrm{D}}(t)),\zeta) : \boldsymbol{e}(\boldsymbol{u}_{\mathrm{D}}(t)) + \frac{\kappa}{r} |\nabla\zeta|^{r} \,\mathrm{d}x \\
= \int_{\Omega} \frac{1}{2} \boldsymbol{\mathfrak{T}}_{\zeta} \boldsymbol{e}(\boldsymbol{u}_{\mathrm{D}}(t)) : \boldsymbol{e}(\boldsymbol{u}_{\mathrm{D}}(t)) + \frac{\kappa}{r} |\nabla\zeta|^{r} \,\mathrm{d}x.$$
(3.28)

In particular,  $u_{\rm D} \in C^1([0,T]; W^{1,2}(\Omega; \mathbb{R}^d))$  implies  $\mathfrak{g}(\cdot, \zeta) \in C^1([0,T])$  for each  $\zeta \in Z$ . Also, by using (3.28) and (2.52), we have the desired formula for the power of external loading:

$$\frac{\partial \boldsymbol{g}}{\partial t}(t,\zeta) = \int_{\Omega} \mathfrak{T}_{\zeta} e(\boldsymbol{u}_{\mathrm{D}}(t)) : e\left(\frac{\partial \boldsymbol{u}_{\mathrm{D}}}{\partial t}\right) \mathrm{d}x$$

$$= \int_{\Omega} \tau(e(\boldsymbol{u}_{\mathrm{D}}(t)),\zeta) : e\left(\frac{\partial \boldsymbol{u}_{\mathrm{D}}}{\partial t}\right) \mathrm{d}x = \int_{\Omega} \mathfrak{s}(t) : e\left(\frac{\partial \boldsymbol{u}_{\mathrm{D}}}{\partial t}\right) \mathrm{d}x. \quad (3.29)$$

The Bochner measurability of  $\mathfrak{s}$  follows from the measurability of  $u_{\varepsilon} : [0,T] \to W^{1,2}(\Omega; \mathbb{R}^d)$  proved in Proposition 3.4 implying measurability of  $\sigma_{\varepsilon} : [0,T] \to L^2(\Omega; \mathbb{R}^{d \times d}_{sym})$  and from the point (iv) together with Pettis' theorem.  $\Box$ 

**Remark 3.8** (Alternative formulation in terms of strains.) Based on formula (2.34), we could define the energetic solution to the complete-damage problem not as a couple  $(\mathfrak{s}, \zeta)$  but as a couple  $(\mathfrak{e}, \zeta)$  with  $\mathfrak{e}(t)$  defined on  $\Omega \setminus N_{\zeta(t)}$  and belonging to the time-dependent locally-convex space  $L^2_{\text{loc}}(\Omega \setminus N_{\zeta(t)}; \mathbb{R}^{d \times d}_{\text{sym}})$ . Taking into account (2.23), the energy equality (3.27) would then take the form

$$\boldsymbol{g}(t_2,\zeta(t_2)) + \operatorname{Var}_R(\zeta;t_1,t_2) = \boldsymbol{g}(t_1,\zeta(t_1)) + \int_{t_1}^{t_2} \int_{\Omega \setminus N_{\zeta(t)}} \zeta \varphi'_e(\boldsymbol{\mathfrak{e}}) : e\left(\frac{\partial u_{\mathrm{D}}}{\partial t}\right) \,\mathrm{d}x \,\mathrm{d}t, \quad (3.30)$$

**Remark 3.9** (Direct  $\Gamma$ -limit convergence.) In terms of  $\zeta$  only, we could obtain existence of the energetic solutions and convergence of solutions of our  $\varepsilon$ -regularized problem by using abstract results about  $\Gamma$ -limits, see [29, Theorem 3.1]. In fact, [29, Assumptions (2.9)–(2.10)] had been proved here in Section 2, [29, Assumption (2.8)] can be easily verified if  $w \in C^1(I; W^{1/2,2}(\Gamma))$ , and [29, Assumptions (2.11)] had been proved in [27], while the other assumptions in [29] are satisfied quite obviously. However, by this way, we would lose tack on the mechanical interpretation involving stress; in particular, the key information in (3.29) would be completely out.

**Remark 3.10** (*Numerical strategies.*) The regularized problem introduced in Section 3.1 suggests a direct numerical treatment: applying implicit discretization in

time with a time step  $\tau > 0$  and, considering a polyhedral domain  $\Omega$  triangulated by simplicial finite elements with a mesh-parameter h > 0, applying P1-finite elements for spatial discretization of both u and  $\zeta$  (let us denote the corresponding discrete spaces  $U_h$  and  $Z_h$ , respectively), we get a recursive coercive mathematicalprogramming problem with a nonlinear objective and box-constraints for  $(u_{\tau h \varepsilon}^k, \zeta_{\tau h \varepsilon}^k)$ :

$$\begin{array}{ll}
\text{Minimize} & \int_{\Omega} \frac{\zeta_{\tau h \varepsilon}^{k} + \varepsilon}{2} \mathbb{C}e(\nabla u_{\tau h \varepsilon}^{k}) : e(\nabla u_{\tau h \varepsilon}^{k}) - a\zeta_{\tau h \varepsilon}^{k} + \frac{\kappa}{r} |\nabla \zeta_{\tau h \varepsilon}^{k}|^{r} \, \mathrm{d}x \\
\text{subject to} & 0 \leq \zeta \leq \zeta_{\tau h \varepsilon}^{k-1}, \ u_{\tau h \varepsilon}^{k}|_{\Gamma} = w(k\tau), \\
& u_{\tau h \varepsilon}^{k} \in U_{h}, \quad \zeta_{\tau h \varepsilon}^{k} \in Z_{h}
\end{array} \right\}$$

$$(3.31)$$

for  $k = 1, ..., K := T/\tau$  with  $(u_{\tau h \varepsilon}^0, \zeta_{\tau h \varepsilon}^0) := (u_0, \zeta_0)$ . This is an implementable conceptual algorithm. Unfortunately, it does not have a quadratic cost functional, which makes it not entirely simple for numerical treatment; for a similar problem with trilinear objectives we refer to numerical simulations in [20]. On the other hand, the approximate solution  $(u_{\tau h \varepsilon}, \zeta_{\tau h \varepsilon})$  considered as a piece-wise constant interpolant  $(u_{\tau h \varepsilon}(t), \zeta_{\tau h \varepsilon}(t)) := (u_{\tau h \varepsilon}^k, \zeta_{\tau h \varepsilon}^k)$  for  $t \in ((k-1)\tau, k\tau]$  has a guaranteed convergence (in terms of suitable subsequences), based on the abstract results from [29, Theorem 3.3], cf. also [28, Sect.5.5].

**Remark 3.11** (Bourdin's approach to cracks.) A functional that is of a similar type as (3.31), namely  $\int_{\Omega} (\zeta + \varepsilon^{\alpha}) \varphi(\nabla u) + \varepsilon |\nabla \zeta|^2 + \varepsilon^{-\beta} (1-\zeta) dx$ , was used in the context of approximation of Francfort-Marigo's crack model [4, 5]. At least for fixed  $\varepsilon > 0$  the mathematical properties of that functional are exactly as those of ours. However, suitable scalings in  $\varepsilon$  yields in the limit  $\varepsilon \to 0$  the mentioned crack problem.

## 4 A one-dimensional example

Let us illustrate the above introduced objects on a one-dimensional situation, having an interpretation of a bar undergoing a tension/compression experiment by a "harddevice" loading, where all mathematical objects can be described explicitly. We consider a bar of the length L fixed at the end-points with a (possibly spatially varying) elastic modulus  $\mathbb{C}$  (that may reflect a possibly varying thickness of the bar). Let us thus put d := 1,  $\Omega := (0, L)$ ,  $\Gamma := \partial \Omega = \{0, 1\}$ ,  $w(0) := w_0$ ,  $w(L) := w_L$ , and now  $\mathbb{C} : (0, L) \to \mathbb{R}^+$ . In accord with (2.6b),  $\mathbb{C}(x) \ge \eta > 0$  for a.a.  $x \in (0, L)$ .

#### 4.1 Static case

Minimization of

$$V_{\varepsilon}(u,\zeta) = \int_{0}^{L} (\zeta(x) + \varepsilon) \frac{\mathbb{C}(x)}{2} \left(\frac{\mathrm{d}u}{\mathrm{d}x}\right)^{2} \mathrm{d}x$$
(4.1)

on  $\{u \in W^{1,2}(0,L); u(0) = w_0, u(L) = w_L\}$  gives the Euler-Lagrange equation

$$\frac{\mathrm{d}}{\mathrm{d}x}\Big((\zeta(x)+\varepsilon)\mathbb{C}(x)\frac{\mathrm{d}u}{\mathrm{d}x}\Big) = 0 \quad \text{on} \quad (0,L).$$
(4.2)

The stress  $\sigma_{\varepsilon} = (\zeta + \varepsilon)\mathbb{C}\frac{\mathrm{d}}{\mathrm{d}x}u$  is thus necessarily constant along the whole bar, and its value can be calculated by using  $\zeta + \varepsilon \ge \varepsilon > 0$  and

$$w_L - w_0 = u(L) - u(0) = \int_0^L \frac{\mathrm{d}u}{\mathrm{d}x} \,\mathrm{d}x = \int_0^L \frac{\sigma_\varepsilon}{(\zeta(x) + \varepsilon)\mathbb{C}(x)} \,\mathrm{d}x. \tag{4.3}$$

Thus we find the formulas for the (constant) stress and for the strain:

$$\sigma_{\varepsilon} = \mathcal{H}\big((\zeta + \varepsilon)\mathbb{C}\big)\frac{w_L - w_0}{L} \quad \text{and} \quad \frac{\mathrm{d}u}{\mathrm{d}x} = \frac{w_L - w_0}{L}\frac{\mathcal{H}\big((\zeta + \varepsilon)\mathbb{C}\big)}{(\zeta(x) + \varepsilon)\mathbb{C}(x)}, \quad (4.4)$$

where  $\mathcal{H}$  denotes the *harmonic mean* of an indicated profile over the interval [0, L], i.e.

$$\mathcal{H}(z) := \frac{1}{\frac{1}{L} \int_0^L \frac{\mathrm{d}x}{z(x)}} \,. \tag{4.5}$$

In particular, we find the explicit formula for  $g_{\varepsilon}$  from (2.10):

$$g_{\varepsilon}(\zeta) = \mathcal{H}((\zeta + \varepsilon)\mathbb{C})\frac{(w_L - w_0)^2}{2L} .$$
(4.6)

Similarly, the functional  $f_{\varepsilon}$  from (2.37) as a quadratic function of  $e_{\rm D} \in L^2(0, L)$  can explicitly be written down as:

$$f_{\varepsilon}(e_{\rm D},\zeta) = \frac{\mathcal{H}((\zeta+\varepsilon)\mathbb{C})}{2L} \left(\int_{0}^{L} e_{\rm D}(x) \,\mathrm{d}x\right)^{2}.$$
(4.7)

The counterexample from Section 2.2 (where L = 2 and  $\mathbb{C} = 1$  were considered) is easily obtained by letting  $\zeta(x) := |x - L/2|^{\alpha}$ . Clearly,

$$\lim_{\varepsilon \to 0+} g_{\varepsilon}(\zeta) = g_0(\zeta) = \mathcal{H}(\zeta \mathbb{C}) \frac{(w_L - w_0)^2}{2L}.$$
(4.8)

However the  $\Gamma$ -limit  $\mathfrak{f}(e_{\mathrm{D}},\zeta)$  vanishes for this particular damage profile  $\zeta$ . Indeed, for all  $\delta > 0$ , we have  $(\zeta - \delta)^+ = 0$  on the interval  $[L/2 - \delta^{1/\alpha}, L/2 + \delta^{1/\alpha}]$  and therefore by (4.8) and (2.42):

$$\mathcal{F}(\varepsilon,\delta,e_{\mathrm{D}},\zeta) = \frac{(w_L - w_0)^2}{2\int_0^L \frac{\mathrm{d}x}{((\zeta(x) - \delta)^+ + \varepsilon)\mathbb{C}(x)}} \le \frac{(w_L - w_0)^2}{2\int_{L/2 - \delta^{1/\alpha}}^{L/2 + \delta^{1/\alpha}} \frac{\mathrm{d}x}{\varepsilon\mathbb{C}(x)}} \le \frac{(w_L - w_0)^2}{4} \|\mathbb{C}\|_{L^{\infty}(0,L)} \frac{\varepsilon}{\delta^{1/\alpha}}$$

so that the limit in  $\varepsilon$  already vanishes. By using the same reasoning for a general  $\zeta \in Z$ , one checks easily that  $\mathfrak{f}(e_{\mathrm{D}}, \zeta)$  is given as follows:

$$f(e_{\rm D},\zeta) = \frac{(w_L - w_0)^2}{2} \begin{cases} 1/\int_0^L \frac{\mathrm{d}x}{\zeta(x)\mathbb{C}(x)} & \text{if } \min_{[0,L]}\zeta(\cdot) > 0, \\ 0 & \text{if } \min_{[0,L]}\zeta(\cdot) = 0. \end{cases}$$
(4.9)

Note that  $\mathfrak{f}(e_{D}, \cdot) : Z \to \mathbb{R}^{+}$  is not continuous in the strong topology of  $W^{1,r}(0, L)$ , r > 1.

This example can also be used to show that the set  $\mathfrak{S}(t,\zeta)$  of realizable stresses may contain more than one stress distribution. For this, take any  $\zeta \in Z$  such that  $\int_0^L \frac{dx}{\zeta(x)\mathbb{C}(x)}$  is finite. Now, choosing  $\zeta_{\varepsilon} \equiv \zeta$ , we find the stress  $\sigma_{\varepsilon}$  from (4.4) and the limit reads  $\sigma_0 = (w_L - w_0) / \int_0^L \frac{dx}{\zeta(x)\mathbb{C}(x)}$ . On the other hand, for a suitable sequence  $\delta_{\varepsilon} \to 0+$ , the sequence  $\hat{\zeta}_{\varepsilon} = (\zeta - \delta_{\varepsilon})^+$  satisfies  $\int_0^L \frac{dx}{(\zeta_{\varepsilon}(x)+\varepsilon)\mathbb{C}(x)} \to 0$  and the corresponding stresses  $\hat{\sigma}_{\varepsilon}$  converge to zero. Thus  $\mathfrak{S}(t,\zeta)$  contains at least two constant stress profiles. In fact, it is not difficult to see that all intermediate constant stresses are realizable, that is

$$\mathfrak{S}(t,\zeta) = \begin{cases} \left\{ \sigma \text{ constant; } 0 \leq \sigma(\cdot) \leq \sigma_0 \right\} \text{ under tension, i.e. if } w_L \leq w_0, \\ \left\{ \sigma \text{ constant; } 0 \geq \sigma(\cdot) \geq \sigma_0 \right\} \text{ under compression, i.e. } w_L \geq w_0. \end{cases}$$

The *effective stress* is obviously *zero*. This is well intuitive for tension experiment but a bit paradoxical for a pressure experiment, but this is a usual consequence of (infinitesimally) small strain concept.

This is a general observation that, as the stress distributions are constant in this 1-dimensional case, the set of  $\mathfrak{S}(t,\zeta)$  realizable stresses is composed from constants and is therefore linearly ordered and thus always a minimizer in (2.32), i.e. the *effective stress, is unique.* 

#### 4.2 Stability

Further, we investigate the global stability of the undamaged state  $\zeta = 1$ . For simplicity, we consider r = 2 and homogeneous material, i.e. constant coefficients  $\mathbb{C}$ , a, and  $\kappa$ . Let us abbreviate

$$\zeta_{\min} := \min_{0 \le x \le L} \zeta(x) \quad \text{and} \quad \zeta_{\max} := \max_{0 \le x \le L} \zeta(x). \tag{4.10}$$

**Lemma 4.1** Let  $E(\zeta) := \int_0^L \frac{\kappa}{2} |\frac{\mathrm{d}}{\mathrm{d}x}\zeta|^2 + a(1-\zeta) \,\mathrm{d}x$  and  $z \in [0,1)$ , then we have

$$\min\left\{E(\zeta); \ \zeta \in \mathbb{Z}, \ \zeta_{\min} = z\right\} = aL\lambda\left(z, \frac{\sqrt{aL}}{\sqrt{2\kappa}}\right)$$
(4.11)

with

$$\lambda(z,\varrho) = \begin{cases} 1 - z - \varrho^2/3 & \text{for } 0 < \varrho \le \sqrt{1-z}, \\ 2(1-z)^{3/2}/(3\varrho) & \text{for } \varrho \ge \sqrt{1-z}. \end{cases}$$
(4.12)

*Proof.* Since E is coercive on  $Z \subset W^{1,2}((0,L))$ , and convex, there is a minimizer  $\zeta_*$  on the weakly closed (but non-convex!) set  $\{\zeta \in Z; \zeta_{\min} = z\}$ .

As the integrand of E is decreasing in  $\zeta$  because a > 0, it is easy to see that the graph of  $\zeta_*$  on any interval  $[x_1, x_2]$  has to lie above the segment connecting  $(x_1, \zeta_*(x_1))$  and  $(x_2, \zeta_*(x_2))$  if  $\zeta_*(\cdot) > z$  on  $[x_1, x_2]$ , i.e. the value  $\zeta_*(\cdot) = z$  is attained somewhere outside  $[x_1, x_2]$ . Hence,  $\zeta_*$  has at most one point  $x_* \in [0, L]$  such that  $\zeta_*(x_*) = z$  if z < 1, and it is strictly concave on both  $[0, x_*]$  and  $[x_*, L]$ .

After some rather lengthy algebra, the formula (4.12) is obtained by assuming  $x_* = 0$  (or, equally,  $x_* = L$ ). For small L, we obtain a solution satisfying  $\frac{d}{dt}\zeta_*(L) = 0$  and  $\zeta_*(L) < 1$ . For larger L, we have  $\zeta_*(x) = 1$  for  $x \ge \sqrt{2\kappa/a}$ .

The condition  $\zeta_*(x_*) = z$  with  $x_* \in (0, L)$  then leads to  $aL\lambda(z, \sqrt{aL}/\sqrt{2\kappa}) + a(L-x_*)\lambda(z, \sqrt{a}(L-x_*)/\sqrt{2\kappa})$  as the minimal value of  $E(\zeta)$  under the (convex) condition  $\zeta(x_*) = z, \zeta \in Z$ . The concavity of  $\xi \mapsto \xi\lambda(z, \xi/\sqrt{2a\kappa})$  now implies that only  $x_* = 0$  or  $x_* = L$  can be optimal.

To study the stability of the undamaged state  $\zeta = 1$  at a specific (and now considered fixed) time t, we define

$$m(\gamma) := \min_{\zeta \in \mathbb{Z}} J_{\gamma}(\zeta) \quad \text{with}$$
  
$$J_{\gamma}(\zeta) := \gamma \mathcal{H}_{0}(\zeta) + E(\zeta) \quad \text{and} \quad \mathcal{H}_{0}(\zeta) := \begin{cases} \mathcal{H}(\zeta) & \text{if } \zeta_{\min} > 0, \\ 0 & \text{if } \zeta_{\min} = 0, \end{cases}$$
(4.13)

where E from Lemma 4.1,  $\mathcal{H}$  from (4.5) and

$$\gamma = \gamma(t) := \mathbb{C} \frac{\ell(t)^2}{2L} \ge 0 \quad \text{with} \quad \ell(t) := w(t, L) - w(t, 0) \quad (4.14)$$

is the energy stored in the body if no damage would occur, i.e. if  $\zeta \equiv 1$ ; of course, we then have  $J_{\gamma}(1) = \gamma$ . Note that  $E, \gamma, J_{\gamma}$ , and m have a physical dimension as energy (i.e.  $J = \text{kg m}^2 \text{s}^{-1}$ ), while  $\lambda, \zeta, z$ , and  $\varrho = \sqrt{aL}/\sqrt{2\kappa}$  have a dimension 1. Also,  $\gamma = g_0(1)$  with  $g_0$  from (2.10) with  $\varepsilon = 0$  or in the evolution context, equivalently,  $\gamma = \min_{u \in W^{1,2}([0,L])} \mathcal{G}_0(t, \cdot, 1)$  with  $\mathcal{G}_0$  from (3.1).

Also, we can see that stability of  $\zeta = 1$  at time t is equivalent to  $m(\gamma) = \gamma$  whereas  $m(\gamma) < \gamma$  means that the (global!) stability of  $\zeta$  is lost.

**Proposition 4.2** (Some conditions for stability of the undamaged state.) Let us define functions  $\Lambda_1, \Lambda_2 : \mathbb{R}^+ \to [0, 1]$  (of physical dimension 1) by

$$\Lambda_1(\varrho) := \frac{2}{4+3\varrho} \quad and \quad \Lambda_2(\varrho) := \begin{cases} 1-\varrho^2/3 & \text{if } 0 < \varrho \le 1, \\ 2/(3\varrho) & \text{if } \varrho \ge 1. \end{cases}$$
(4.15)

Then we have  $\Lambda_1(\varrho) < \Lambda_2(\varrho)$  and (i)  $\gamma > aL\Lambda_2(\sqrt{aL}/\sqrt{2\kappa})$  implies  $m(\gamma) < \gamma$ , i.e.  $\zeta = 1$  is not globally stable, (ii)  $\gamma \leq aL\Lambda_1(\sqrt{aL}/\sqrt{2\kappa})$  implies  $m(\gamma) = \gamma$ , i.e.  $\zeta = 1$  is globally stable.

*Proof.* Part (i) follows easily by using the minimizers of Lemma 1 for  $z \in (0, L)$  and then taking the limit  $z \to 0$ .

For Part (ii), the argument is more involved. First, note that a global minimizer  $\zeta_{\gamma}$  of  $J_{\gamma}$  in Z must exist. As we only consider  $0 < \gamma \leq aL\Lambda_1(\sqrt{aL}/\sqrt{2\kappa})$  and  $\Lambda_1 \leq \Lambda_2$ , we use the arguments of Part (i) to conclude that  $[\zeta_{\gamma}]_{\min} > 0$ , and hence  $\zeta_{\gamma}$  solves the Neumann boundary-value problem for the following differential inclusion:

$$-\kappa \frac{\mathrm{d}^2 \zeta}{\mathrm{d}x^2} - a + \frac{\gamma \mathcal{H}(\zeta)^2}{L} \frac{1}{\zeta^2} + \partial \chi_{(-\infty,1]}(\zeta) \ge 0, \quad \frac{\mathrm{d}\zeta}{\mathrm{d}x}(0) = 0 = \frac{\mathrm{d}\zeta}{\mathrm{d}x}(L). \tag{4.16}$$

By [19, Chap.3, Theorem 2.3], each solution lies in  $W^{2,p}((0,L))$ ,  $p < +\infty$  arbitrary; possibly it has a flat part with  $\zeta(\cdot) = 1$ .

Testing (4.16) by  $\frac{\mathrm{d}}{\mathrm{d}x}\zeta$  gives

$$\frac{\kappa}{2} \left| \frac{\mathrm{d}\zeta}{\mathrm{d}x} \right|^2 + a\zeta + \frac{\gamma \mathcal{H}(\zeta)^2}{L} \frac{1}{\zeta^2} = ac \tag{4.17}$$

for a suitable constant c. Note that this also holds if the "reaction force" from  $\partial \chi_{(-\infty,1]}(\zeta)$  does not vanish. It holds either  $\zeta = 1$  (and then (4.17) is trivial) or  $0 < \zeta_{\min} < 1$ . In the latter case,  $\frac{d}{dx}\zeta(x) = 0$  whenever  $\zeta(x) = 1$  and (4.17) again holds on [0, L].

Now, assume  $0 < \zeta_{\min} \leq \zeta_{\max} \leq 1$ . Then inserting these values into (4.17) (using that  $\frac{d}{dx}\zeta(\cdot) = 0$  when these values are attained) gives

$$a\zeta_{\max} + \frac{\gamma \mathcal{H}(\zeta)^2}{L} \frac{1}{\zeta_{\max}} = ac = a\zeta_{\min} + \frac{\gamma \mathcal{H}(\zeta)^2}{L} \frac{1}{\zeta_{\min}}.$$
(4.18)

First, consider  $\zeta_{\min} = \zeta_{\max}$ , then  $\zeta \equiv \zeta_{\min}$  and  $J_{\gamma}(\zeta_{\min}) = \gamma + (aL-\gamma)(1-\zeta_{\min})$ . Because of  $\gamma < aL$ , we have  $J_{\gamma}(\zeta_{\min}) > J_{\gamma}(1)$  for  $\zeta_{\min} < 1$ . Hence we have a contradiction. Second, assuming that we have a minimizer with  $\zeta_{\min} < \zeta_{\max} \leq 1$ , we conclude from (4.18) that

$$c = \zeta_{\min} + \zeta_{\max}$$
 and  $\mathcal{H}(\zeta)^2 = \frac{aL}{\gamma} \zeta_{\min} \zeta_{\max}.$  (4.19)

Using  $\mathcal{H}(\zeta) \leq \zeta_{\max}$  and  $\zeta_{\max} \leq 1$ , we find  $\zeta_{\min} \leq \gamma/(aL)$ . Now, using  $J_{\gamma}(\zeta) \geq \mathcal{E}(\zeta)$ , we may employ Lemma 4.1 and find  $J_{\gamma}(\zeta_{\gamma}) \geq aL\lambda(\gamma/(aL), \sqrt{aL/\sqrt{2\kappa}})$ . Some elementary calculations show that  $\gamma \leq aL\Lambda_1(\sqrt{aL}/\sqrt{2\kappa})$  implies  $aL\lambda(\gamma/(aL), \sqrt{aL/\sqrt{2\kappa}}) > \gamma$ . In fact, since  $\gamma \mapsto \lambda(\gamma/(aL), \varrho)$  strictly decreases on [0, aL] and attains the value 0 at  $\gamma = aL$ , there is a unique solution  $\gamma_*$  of  $\gamma = \lambda(\gamma/(aL), \varrho)$  and  $J_{\gamma}(\zeta_{\gamma}) \geq \gamma$  holds for any  $\gamma \in [0, \gamma_*]$ . An explicit calculation gives  $\gamma_* = aL\Lambda(\sqrt{aL/\sqrt{2\kappa}})$ , where  $\Lambda(\varrho)$  is the unique solution of  $z = \lambda(z, \varrho)$ . We find  $\Lambda(\varrho) = 1/2 + \varrho^2/6$  for  $\varrho^2 \leq 3/7$  and the estimate  $\Lambda(\varrho) \geq 2/(3(1+\varrho))$  for  $\varrho^2 \geq 3/7$ . Hence we obtain a contradiction to the assumption that a nontrivial (i.e. not identically 1) global minimizer exists, and Part (ii) is proved.

#### 4.3 Evolution conjectured

We conjecture that the bound  $\Lambda_2$  in Proposition 4.2 is sharp, i.e. the upper bound  $\Lambda_1$  can be replaced by  $\Lambda_2$ . In such case, we could give an exact solution for the

1-dimensional damage evolution problem as follows. We now consider  $\gamma = \gamma(t)$  evolving in time, cf. (4.14).

Consider  $\mathfrak{g}(t,\zeta) = \gamma(t)\mathcal{H}_0(\zeta) + \int_0^L \frac{\kappa}{2} |\frac{\mathrm{d}}{\mathrm{d}t}\zeta|^2 \mathrm{d}x$  and R as before, cf. (4.13)–(4.14) and (3.2). The prescribed elongation/shrinkage  $\ell(t)$  is continuous, cf. (3.16) where even  $C^1$ -smoothness was assumed. Let  $\ell$  be strictly monotone, say decreasing, in time, starting from  $\ell(0) = 0$ , and the body is initially undamaged and undeformed, i.e.  $\zeta_0 \equiv 1$  and  $u_0 \equiv 0$ , which is compatible with (3.17). Then

$$\zeta(t,x) = \begin{cases} 1 & \text{for } 0 \le t < t_*, \ x \in [0,L], \\ \zeta_{\text{dam}}(x) & \text{for } t \ge t_*, \quad x \in [0,L], \end{cases}$$
(4.20)

where  $t_*$  is the unique value such that

$$\ell(t_*)^2 = \frac{2a}{\mathbb{C}} L^2 \Lambda_2 \left(\frac{\sqrt{aL}}{\sqrt{2\kappa}}\right) \tag{4.21}$$

and where  $\zeta_{\text{dam}}$  is one of the two minimizers of E under the constraint  $\zeta_{\min} = 0$ , cf. (4.11) with z = 0. We have immediate total damage at one point since the instability criterion in Proposition 4.2(i) is obtained by complete damage. From (4.21), we can identify a *critical strain*  $e_{\text{crit}} := |\ell(t_*)|/L$  above which the (even total) damage starts evolving, namely

$$e_{\rm crit} := \frac{|\ell(t_*)|}{L} = \sqrt{\frac{2a}{\mathbb{C}}} \Lambda_2\left(\frac{\sqrt{aL}}{\sqrt{2\kappa}}\right)$$
(4.22)

For very short bars, i.e. small L, we have asymptotically  $\rho = \sqrt{aL}/\sqrt{2\kappa} \to 0$  and then  $\Lambda_2(\rho) \to 1$ , cf. (4.15), so that, from (4.22), we can see that

$$e_{\rm crit} \approx \sqrt{2a/\mathbb{C}}.$$
 (4.23)

In particular, we can see that the resistivity to damage is determined by the ratio (physically of dimension 1) of the activation stress and the elastic modulus, while  $\kappa > 0$  plays (asymptotically) no role as well as the length L itself.

Conversely, for long bars, in particular for  $L \ge \sqrt{2\kappa/a}$ , we have  $\rho = \sqrt{aL}/\sqrt{2\kappa} \ge 1$ and thus  $\Lambda_2(\rho) = 2/(3\rho)$ , cf. (4.15), so that, substituting it into (4.22), we can see that

$$e_{\rm crit} = 2 \frac{\sqrt[4]{2a\kappa}}{\sqrt{3L\mathbb{C}}}.$$
(4.24)

In particular, we can see that  $e_{\rm crit}$  decays with increasing length L as  $\mathcal{O}(1/\sqrt{L})$ . A paradoxical effect can thus be expected (at least asymptotically if  $L \to \infty$ ) that the bar tends to break already even when a very small strain is achieved by the loading (although the boundary displacement, i.e. the loading  $\ell(t_*) = e_{\rm crit}L \approx \sqrt{L}$  itself, must be sufficiently large). This effect is caused be the adopted concept of global stability (3.13) which is ultimately favorite for damage at small spots if there is

enough energy stored in the whole body. Fortunately, large engineering workpieces (as e.g. long bridges or tall towers) rely rather on local stability principles for which, however, a rigorous mathematical theory is not developed yet. This reveals certain limits of applications the presented model.

Acknowledgment: The second author acknowledges the support from C18-subproject of the Research center "Matheon" (Deutsche Forschungsgemeinshaft). The third author acknowledges the hospitality of the Université Sud Toulon–Var and of the Weierstraß Institut, Berlin, where majority of this research has been carried out, in the latter case supported through the Alexander von Humboldt Foundation. Partial support of this research from the grants IAA 1075402 (GA AV ČR), and LC 06052 and MSM 21620839 (MŠMT ČR) as well as from the European grants HPRN-CT-2002-00284 "Smart systems" and MRTN-CT-2004-505226 "Multi-scale modelling and characterisation for phase transformations in advanced materials" is acknowledged, too.

## References

- E. Benvenuti, G. Borino, A. Tralli: A thermodynamically consistent nonlocal formulation for damaging materials, *Euro. J. Mech. A/Solids* 21 (2001) 535-553.
- [2] E. Bonnetti, G. Schimperna: Local existence for Frémond model of damage in elastic materials. Cont. Mech. Thermodyn. 16 (2004) 319-335.
- G. Bouchitté, M. Valadier: Integral representation of convex functional on a space of measures. J. Funct. Anal. 80 (1988), 398-420.
- [4] B. Bourdin: The variational formulation of brittle fracture: numerical implementation and extensions. In: *IUTAM Symp. Discretization Meth. for Evolving Discontinuities*. (T. Belytschko, A. Combescure, R. de Borst, eds.), Springer, 2007. (to appear)
- [5] B. Bourdin, G.A. Francfort, J.-J. Marigo: Numerical experiments in revisited brittle fracture. J. Mech. Phys. Solids 48 (2000), 797-826.
- [6] G. Dal Maso: An Introduction to  $\Gamma$ -convergence. Birkhäuser, 1995.
- [7] G. Dal Maso, G. Francfort, R. Toader: Quasistatic crack growth in nonlinear elasticity. Arch. Rat. Mech. Anal. 176 (2005), 165-225.
- [8] R. De Borst, A. Benallal, O.M. Heeres: A gradient-enhanced damage approach to fracture. J. de Physique IV 6 (1996) C6, 491-509.
- [9] A. DeSimone, J.-J. Marigo, L. Teresi: A damage mechanism approach to stress softening and its application to rubber. *Eur. J. Mech. A/Solids* 20 (2001) 873-892.
- [10] E.A. De Souza Neto, D. Peric, D.R.J. Owen: A phenomenological three-dimensional rate-independent continuum damage model for highly filled polymers: Formulation and computational aspects. J. Mech. Phys. Solids 42 (1994) 1533-1550.
- [11] G.A. Francfort, A. Garroni: A variational view of partial brittle damage evolution. Arch. Rat. Mech. Anal. 182 (2006), 125–152.
- [12] G. Francfort, A. Mielke: An existence result for a rate-independent material model in the case of nonconvex energies. J. reine u. angew. Math. 595 (2006), 55–91.
- [13] M. Frémond: Non-smooth thermomechanics. Springer, Berlin, 2002.

- [14] M. Frémond, K.L. Kuttler, B. Nedjar, M. Shillor: One-dimensional models of damage. Adv. Math. Sci. Appl. 8 (1998) 541-570.
- [15] M. Frémond, K.L. Kuttler, M. Shillor: Existence and uniqueness of solutions for a dynamic one-dimensional damage model. J. Math. Anal. Appl. 229 (1999) 271-294.
- [16] M. Frémond, B. Nedjar: Damage in concrete: the unilateral phenomenon. Nucl. Eng. Des. 156 (1995) 323-335.
- [17] M. Frémond, B. Nedjar: Damage, gradient of damage and principle of virtual power. Int. J. Solid Struct. 33 (1996) 1083-1103.
- [18] S. Govindjee, J.C. Simo: A micro-mechanically based continuum damage model for carbon black-filled rubbers incorporating Mullins' effect. J. Mech. Phys. Solids 39 (1991) 87-112.
- [19] D. Kinderlehrer, G. Stampacchia: An Introduction to Variational Inequalities and their Applications. Academic Press, New York, 1980.
- [20] M. Kočvara, A. Mielke, T. Roubíček: A rate-independent approach to the delamination problem. *Mathematics and Mechanics of Solids* 11 (2006), 423-447.
- [21] V.I. Levitas: The postulate of realizibility: formulation and applications to postbifurcational behavior and phase transitions in elastoplastic materials. Int. J. Eng. Sci. 33 (1995), 921–971.
- [22] E. Lorentz, S. Andrieux: A variational formulation for nonlocal damage models. Int. J. of Plasticity 15 (1999) 119-138
- [23] G.A. Maugin: The thermodynamics of plasticity and fracture. Cambridge Univ. Press, Cambridge, 1992.
- [24] C. Miehe: Discontinuous and continuous damage evolution in Ogden-type large-strain elastic materials. Eur. J. Mech., A 14 (1995) 697-720.
- [25] C. Miehe, J. Keck: Superimposed finite elastic-viscoelastic-plastoelastic stress response with damage in filled rubbery polymers. Experiments, modelling and algorithmic implementation. J. Mech. Phys. Solids 48 (2000) 323-365.
- [26] A. Mielke: Evolution of rate-independent systems. In: Handbook of Differential Equations: Evolutionary Diff. Eqs. (Eds. C.Dafermos, E.Feireisl), pp. 461–559, Elsevier, Amsterdam, 2005.
- [27] A. Mielke, T. Roubíček: Rate-independent damage processes in nonlinear elasticity. Math. Models and Meth. in Appl. Sci. 16 (2006), 177-209.
- [28] A. Mielke, T. Roubíček: Numerical approaches to rate-independent processes and applications in inelasticity. (Preprint No.1169, WIAS, Berlin, 2006.) Math. Modelling Numer. Anal., submitted.
- [29] A. Mielke, T. Roubíček, U. Stefanelli: Γ-limits and relaxation for rate-independent evolutionary problems. (Preprint no.1156, WIAS Berlin, 2006.) Calc. Var., submitted.
- [30] A. Mielke, F. Theil: A mathematical model for rate-independent phase transformations with hysteresis. In: *Models of continuum mechanics in analysis and engineering*. (Eds.: H.-D.Alber, R.Balean, R.Farwig), Shaker Ver., Aachen, 1999, pp.117-129.
- [31] A. Mielke, F. Theil, V.I. Levitas: A variational formulation of rate-independent phase transformations using an extremum principle. Archive Rat. Mech. Anal. 162 (2002), 137–177.
- [32] U. Mosco: Convergence of convex sets and of solutions of variational inequalities. Adv. in Math. 3 (1969), 510-585.

- [33] M. Ortiz: An analytical study of the localized failure modes of concrete. Mech. Mater. 6 (1987) 159-174.
- [34] H. Stumpf, K. Hackl: Micromechanical concept for the analysis of damage evolution in thermo-viscoelastic and quasi-bittle materials. Int. J. Solids Structures 40 (2003), 1567–1584.
- [35] A. Visintin: Strong convergence results related to strict convexity. Comm. Partial Diff. Equations 9 (1984), 439-466.